Air Velocity in a Pipe

Using the equation and typical values of V, D, and L explained to the right approximate values of P are computed as follows:

Velocity Ft / Sec	Pipe Diameter in Inches, 10' long						
	1	2	4	6	10		
1	.0004	.0002	.0001	.00007	.00004		
2	.0016	.0008	.0004	.00030	.00016		
5	.0100	.0050	.0025	.00170	.0010		
10	.0400	.0200	.0100	.00670	.0040		
15	.0900	.0450	.0225	.01500	.0090		
20	.1600	0080	.0400	.02700	.0160		
25	.2500	.1250	.0625	.04170	.0250		
30	.3600	.1800	.0900	.06000	.0360		

$$V = \sqrt{\frac{25,000 \text{ DP}}{L}}$$

V = air velocity in feet per second

D = pipe inside diameter in inches

L =length of pipe in feet

P = pressure loss due to air friction in ounces/square inch

Air Volume Discharged from Pipe

CFM = air volume in cubic feet per minute

- V = air velocity in feet per second as determined in the equation at the top of this page
- A = cross section area of pipe in square feet

CFM = 60VA

Boyle's Law

If temperature is kept constant, the volume of a given mass of gas is inversely proportional to the pressure which is exerted upon it.

Initial Pressure	=	<u>Final Volume</u>		
Final Pressure	_	Initial Volume		

Air Supply Requirements (operating pressure: 90 PSI)

ΤοοΙ	Class		Hose Size (inches)		
		Typical Air Consumption (CFM)	0 - 10 ft.	10 - 50 ft.	50 - 200 ft
	25 lb.	45	1/2"	1/2"	3/4"
Paving breakers	35 lb.	50	1/2"	3/4"	3/4"
	60 lb.	65	1/2"	3/4"	1"
	80 lb.	80	3/4"	3/4"	1"
Clay diggers		45	1/2"	1/2"	3/4"
l l - u - el - el alutil e	8 lb.	20	3/8"	3/8"	1/2"
Hand drills	15 lb.	32	3/8"	1/2"	1/2"
Rock (sinker) drills	45 lb.	105	3/4"	3/4"	1"
	55 lb.	130	3/4"	1"	1"
Tananana	5" butt	20	3/8"	1/2"	1/2"
Tampers	6" butt	30	1/2"	1/2"	3/4"
Sump pump	3 HP	100	3/4"	3/4"	1″
Sludge pump	Ejector	90	1"	1"	1"
Vibratara	2-1/2"	60	1"	1"	1"
Vibrators	3"	60	1"	1"	1"
Chipping hammers		25	3/8"	1/2"	1/2"
	3/8" sq. dr.	10	5/16"	3/8"	3/8"
Impact wrenches	1/2"	15	5/16"	3/8"	1/2"
	3/4"	25	3/8"	1/2"	1/2"
	1"	50	1/2"	3/4"	3/4"
Drills	1/4" - 1/2"	22	3/8"	3/8"	1/2"
Grinders	die / burr	20	3/8"	3/8"	1/2"
	small angle	20	3/8"	3/8"	1/2"
	3 HP vertical	75	1/2"	3/4"	1"

1120