

## Metal Detectable Clamp Gaskets

**Materials:**

- Metal detectable gaskets are impregnated with stainless steel particles. The addition of stainless steel allows a gasket or gasket pieces to be found with metal detection equipment.


---

### Buna-N

**Features:**

- good general use where temperature extremes do not exist
- minimum temperature: **-20°F (-29°C)**
- maximum temperature: **212°F (100°C)**

Size	Buna-N Part #
1"	<b>40MP-UZ100</b>
1½"	<b>40MP-UZ150</b>
2"	<b>40MP-UZ200</b>
2½"	<b>40MP-UZ250</b>
3"	<b>40MP-UZ300</b>
4"	<b>40MP-UZ400</b>



Type 1 - Standard  
1" and larger


---

### EPDM

**Features:**

- resistant to steam, water and base solutions
- minimum temperature: **-70°F (-57°C)**
- maximum temperature: **310°F (154°C)**

Size	EPDM Part #
1"	<b>40MP-EZ100</b>
1½"	<b>40MP-EZ150</b>
2"	<b>40MP-EZ200</b>
2½"	<b>40MP-EZ250</b>
3"	<b>40MP-EZ300</b>
4"	<b>40MP-EZ400</b>



Type 1 - Standard  
1" and larger


---

### FKM

**Features:**

- resistant to steam, heat and high acid solutions
- minimum temperature: **-20°F (-29°C)**
- maximum temperature: **410°F (410°C)**

Size	FKM Part #
1"	<b>40MP-SFYZ100</b>
1½"	<b>40MP-SFYZ150</b>
2"	<b>40MP-SFYZ200</b>
2½"	<b>40MP-SFYZ250</b>
3"	<b>40MP-SFYZ300</b>
4"	<b>40MP-SFYZ400</b>



Type 1 - Standard  
1" and larger