EZLink™ Armless Cam and Groove

Applications:

- transfer and/or unloading of fuels (gasoline or diesel) from tank truck to storage tanks
- · transfer of liquids compatible with the available coupling and gasket materials

Materials:

- Couplings and dust caps: A356 aluminum, 316 stainless steel
- · Coupler tabs and springs: 316 stainless steel
- · Gasket: Buna-N

Features:

- automatic couplers push-to-connect providing a reliable connection
- low profile allows easy connection and disconnection in tight applications
- · coupler push tabs can be locked with safety pins and/or zip tie
- · compatible with standard cam and groove adapters
- · lifetime warranty on stainless steel tabs

Specifications:

- maximum working pressure with King Crimp™ ferrules: 250 PSI (2"), 150 PSI (3" and 4")
- maximum working pressure with crimp sleeves: 2" 250 PSI, 3" 125 PSI, 4" 110 PSI
- maximum working pressure with band clamps: 2" 250 PSI, 3" 125 PSI, 4" 100 PSI
- gasket temperature range: 5°F to 180°F (-15°C to 82°C)

Only use EZLink™ gaskets and tabs for this coupling system. Traditional cam & groove handles and gaskets, or other types of seals are not compatible and will fail.



Type B Couplers

coupler x male NPT



Size	A356 Aluminum Part #	316 Stainless Steel Part #
1½"	EZL150-B-AL NEW	EZL150-B-SS
2"	EZL200-B-AL	EZL200-B-SS
3"	EZL300-B-AL	EZL300-B-SS NEW
4"	EZL400-B-AL	

Type C Couplers - King Crimp™ Hose Shank

coupler x hose shank



Size	A356 Aluminum Part #	316 Stainless Steel Part #
1½" 2" 3" 4"	EZL150-C-AL EZL200-C-AL EZL300-C-AL EZL400-C-AL	EZL150-C-SS EZL200-C-SS EZL300-C-SS

Type D Couplers

coupler x female NPT



Size	A356 Aluminum Part #	316 Stainless Steel Part #
1½" 2" 3" 4"	EZL150-D-AL EZL200-D-AL EZL300-D-AL EZL400-D-AL	EZL150-D-SS EZL200-D-SS EZL300-D-SS