Omega™ Monitor



Features:

- · cast-in turning vanes for a more efficient flow
- 360° horizontal and 150° vertical travel
- friction loss: 10 PSI at 800 GPM (.7 bar at 3030 LPM)
- 4 bolt hole pattern on flange
- Factory Mutual approved

Size	Inlet	Outlet	Waterway	Flow	<i>Brass</i> Part #
17" x 11½"	3" flange	2½" MNST	3"	1250 GPM	AK3526-300FL

· For flange dimensions, diagrams and additional information please reference dixonvalve.com.



Monitor Nozzle

Features:

- fixed teeth
- · combination Straight, Stream and Fog no shutoff
- · fixed gallonage master stream nozzle
- factory set at 500 GPM (1900 lpm) field changeable to 300 or 700 GPM (1140 or 2660 LPM)
- maximum operating pressure: 100 PSI (water only)

Size	Thread	90° Spray GPM @ 100 PSI	<i>Brass</i> Part #	
2½"	NST (NH)	500	AK4450NST	

• Gaskets are special order, please call 877.712.6179 for assistance.



FirePro™ Monitor

Features:

- seamless 2½" monitor rated at 750 GPM
- · carbon steel construction, stainless steel discharge tip and ball bearings
- 360° horizontal and 140° vertical travel
- · red epoxy finish standard
- 150# ASA raised face 4" flange
- Factory Mutual approved

Size	Inlet	Outlet	Waterway	Flow GPM	Carbon Steel Part #
22" x 13"	4" flange	21/2" MNST	21/2"	750	FP475S

- Gaskets are special order, please call 877.712.6179 for assistance.
- · For flange dimensions, diagrams and additional information please reference dixonvalve.com.



Master Stream Nozzles

Features:

- · factory set at 500 GPM
- featuring a straight stream to fog 'quick throw' pattern change
- · constant gallonage

Size	Thread	Material	Part #
2½"	NST (NH)	brass	FP500B ¹
	NST (NH)	aluminum	FP500A



• Gaskets are special order, please call 877.712.6179 for assistance.



