Wilkerson Miniature Regulators

Features:

- 0-125 PSI adjusting range
- balanced valve design
- self-relieving standard
- non-rising push/pull locking adjustment knob
- two ¼" NPT gauge ports standard on models without gauge, one ¼" NPT gauge port standard on models with gauge can be used for additional outlet ports.
- models with gauge are supplied with a 0-160 flush mount style gauge
- models supplied without gauge use a GC620 gauge.
- panel mount nuts sold separately
- maximum operating conditions:
 - 300 PSIG (20.7 bar) and 32°F to 150°F (0°C to 65.5°C)





Size	Flow	With Gauge		Without Gauge		
	(SCFM)	Part #	Price/E	Part #	Price/E	
1⁄8"	29.2	R08-01RG	\$63.00	R08-01R	\$46.30	
1⁄4"	44 R08-02RG		63.00	R08-02R	46.30	

Wilkerson Miniature Water Regulators

Features:

- 2-125 PSI adjusting range
- suitable for water and compressed air service
- brass construction wetted parts
- non-relieving spring-loaded diaphragm
- panel mount nut included
- two 1/8" NPT gauge ports standard
- models supplied without gauge use a GC620 gauge
- maximum operating conditions: 300 PSIG (20.7 bar) and 40°F to 125°F (4.4°C to 52°C)

(60) 06.2	3.06 (78)	
(113) UC.	1.58 (40)	



Size	Flow	With Gauge		Without Gauge		
	(SCFM)	Part #	Price/E	Part #	Price/E	
1⁄8"	11	RB3-01RG	\$68.00	RB3-01R	\$51.30	
1/4"	14	RB3-02RG	68.00	RB3-02R	51.30	

See pages 229-231 for regulator accessories.

Wilkerson Miniature Filter / Regulators

Features:

- 2-125 PSI adjusting range
- 5 micron element
- .5 oz. bowl
- self-relieving
- supplied with a GC620 gauge
- maximum operating conditions:
- transparent bowl: **125 PSIG** (8.6 bar) and **40°F** to **125°F** (4.4°C to 52°C)
- metal bowl: **300 PSIG** (20.7 bar) and **40°F** to **125°F** (4.4°C to 52°C)





transparent bowl

Size	Flow (SCFM)	With Transparent Bowl and Guard			With Metal Bowl				
		Automatic Drain		Manual Drain		Automatic Drain		Manual Drain	
		Part #	Price/E	Part #	Price/E	Part #	Price/E	Part #	Price/E
1⁄8"	13	BB3-01AG	\$129.85	BB3-01MG	\$119.65	BB3-01AGMB	\$137.75	BB3-01MGMB	\$127.40
1⁄4"	16	BB3-02AG	129.85	BB3-02MG	119.65	BB3-02AGMB	137.75	BB3-02MGMB	127.40

FRL's are designed for air service only, unless otherwise indicated.

SCFM ratings at 150 PSIG inlet pressure.