Dixon™ Keychain



Feature:

halves separate like a coupler and plug

Plated Steel Part #	Price/E
DKC1	\$20.95

Breather Vents

Applications:

- commonly used on single acting cylinders or valves to prevent dirt and foreign particles from entering ports open to the atmosphere additionally
- provide vacuum relief or pressure equalization on gear boxes, oil tanks or reservoirs

Features:

- standard pipe thread connections for quick assembly and removal for cleaning
- nickel plated steel insert with a bronze filter
- 40 micron filter element
- maximum operating pressure: 150 PSI
- temperature range: 35°F to 300°F

NPT Thread	Overall Length	Nickel Plated Steel Part #	Price/E
	-	Fail#	
1/8"	7/16"	ASP-1BV	\$2.50
1/4"	5/8"	ASP-2BV	2.60
3/8"	3/4"	ASP-3BV	3.75
1/2"	7/8"	ASP-4BV	5.50
3/4"	1"	ASP-6BV	8.90
1"	1-5/16"	ASP-8BV	17.20

Conical Mufflers

Application:

- threads into the exhaust ports of air tool, valves, cylinders and other pneumatic equipment
 Features:
- an economical way to reduce noise levels below 90 dBA to conform with OSHA standards
- 40 micron bronze filter element
- element is bonded directly to the fitting and is not replaceable
- maximum operating pressure: 300 PSI
- temperature range: 35°F to 300°F



NPT Thread	Overall Length	Nickel Plated Steel Part #	Price/E
1/8"	11/8"	CMF18	\$3.60
1/4"	1¾"	CMF28	4.30
3/8"	1½"	CMF38	5.60
1/2"	11/8"	CMF48	8.65
3/4"	21/4"	CMF68	14.30
1"	21/8"	CMF88	20.50

Speed Control Mufflers

Features:

- maximum operating pressure: 300 PSI
- temperature range: 35°F to 300°F
- safe and infinite variations of metering air flow at acceptable sound levels on exhaust ports of air valves
- speed of operating cylinder or air tool may be increased or decreased with adjusting screw, the final position is locked in place by the lock nut
- exhaust air noise is eliminated by a surrounding sleeve of sintered bronze







