Steam Quick Disconnect Couplings

Applications:

designed exclusively for steam applications

Features:

- coupler and plug are solid brass with stainless steel springs and locking balls
- coupler has a large plated steel sleeve designed for easier gripping with gloves
- two ethylene propylene O-rings in the coupler and one ethylene propylene O-ring in the plug provide double protection against leaks
- rated to 200 PSI gauge saturated steam (388°F)



Warning: Do Not Disconnect Under Pressure!

poppet valve couplers

	•	
Female NPT Size	Part #	Price/E
1/4"	B16-200S	\$44.92
3/8"	B16-300S	48.39
1/2"	B16-400S	67.52
3/4"	B16-600S	105.71
1"	B16-800S	171.63
1½"	B16-1200S	459.94
	Female NPT Size 1/4" 3/8" 1/2" 3/4" 1"	Female NPT Size Part # 1/4" B16-200S 3/8" B16-300S 1/2" B16-400S 3/4" B16-600S 1" B16-800S



poppet valve plugs

Body Size	Female NPT Size	Part #	Price/E
1/4"	1/4"	B17-200S	\$13.87
3/8"	3/8"	B17-300S	19.63
1/2"	1/2"	B17-400S	24.67
3/4"	3/4"	B17-600S	43.32
1"	1"	B17-800S	56.64
11/2"	1½"	B17-1200S	356.40



Dry Disconnect Fittings for Steam Service

Applications:

 designed to fit hoses carrying steam used in chemical (heating), pharmaceutical (disinfection and sterilization) and at loading bays

Features:

- · coupling housing and all inner parts: stainless steel
- seals: EPDM 291, other materials available, contact Dixon™
- unintentional separation is eliminated preventing accidents and avoiding unintended down time
- performance unaffected by surface rust
- lockable versions are available on 1½" and 2", contact Dixon™
- couplers supplied with double handles

coupler x female NPT

Female NPT	Body Size	316 Stainless Steel Part #	Price/E
3/4"	56 mm	DDSC075SS	\$2956.30
1"	56 mm	DDSC100SS	2956.30
1½"	70 mm	DDSC150SS	3560.45
2"	70 mm	DDSC200SS	3560.45



adapter x female NPT

Female NPT	Body Size	316 Stainless Steel Part #	Price/E
3/4"	56 mm	DDSA075SS	\$832.10
1"	56 mm	DDSA100SS	832.10
1½"	70 mm	DDSA150SS 🕡	1215.60
2"	70 mm	DDSA200SS	1215.60

