Torque Wrenches

Micrometer Adjustable C Series Torque Wrenches



Features:

- 36 tooth quick release ratchet head
- certification readings and individual instrument serial number are included
- Each torque instrument, as calibrated at the factory, is certified to meet the accuracy specified in ANSI B107.14M-1994 and was calibrated on a torque standard that is traceable to the National Institute of Standards Technology (NIST)
- accurate to ±3% and ±5% CCW of full scale

Plated Steel Part #	Drive	Range In-Lb Ft-Lb		Length	Price
C1001	1/4"	20 - 100		11"	\$360.00
C2001	1/4"	40 - 200		16"	360.00
C1002	3/8"		15 - 100	17"	390.00
C1503	1/2"		20 - 150	24"	400.00
C2503	1/2"		30 - 250	24"	420.00

Micrometer Adjustable Heavy Duty Industrial Torque Wrenches



Features:

- 24 tooth quick release ratchet head
- click type wrench
- equipped with ¾" or 1" dual direction quick release, 24 tooth ratchet
- precision roll marked scale
- polished durable bright chrome finish
- · fully repairable and easily calibrated
- calibrated to +/-3% at any setting
- meets ASME B107.14B

Part #	Drive	Range Ft-Lb	Length	Price
C4504	3/4"	50 - 450	41.9"	\$1100.00
C6004	3/4"	100 - 600	49.8"	1250.00
C7504	3/4"	150 - 750	49.8"	1400.00
C6005	1"	100 - 600	49.8"	1320.00
C7505	1"	150 - 750	49.8"	1600.00

Electronic Torque Wrenches

Features:

- 24 tooth quick release ratchet head
- 5 alphanumeric digit display, 4 keys: up, down, mode, unit
- 3 colored lights, vibration and audible alarm
- unit: ft-lb, in-lb and Nm.
- mode: Peak Hold
- torque setting from 5% to 100% of full scale
- accuracy torque ±1% both CW and CCW from 10%-100% of Indicate value
- 2 AA batteries provide up to 500 hours of continuous use
- ISO-6789-2003 and ASME B107-2005 Standard compliant
- Certificate of N.I.S.T. traceability for 10% to 100% of full scale

Part #	Drive	Range		Longth	\\/\dagger	Drice
		In-Lb	Ft-Lb	Length	Wt in Lbs.	Price
DW2501	1/4"	12.5 - 250	1 - 20.7	13"	2.8	\$590.00
DW1002	3/8"	60 - 1200	5 - 100	18"	3.4	590.00
DW2503	1/2"	150 - 3000	12.5 - 250	26.5"	4.8	720.00

