

Synthetic Double Jacket Mill Hose

Application:

- ideal for open end discharge applications, not intended for fire fighting service



Features:

- outer construction: double jacket, all polyester
- tube construction: black, PVC rubber
- rated pressure: **250 PSI** at 70°F
- working pressure: **200 PSI** at 70°F
- double jacket hoses are **not** recommended for use with field reattachable couplings



Uncoupled

Size	Bowl	Length	Part #	Price/E
1½"	1-13/16"	50'	DM15-50UC	\$181.00
1½"	1-13/16"	100'	DM15-100UC	363.00
2"	2-5/16"	50'	DM20-50UC	223.00
2"	2-5/16"	100'	DM20-100UC	445.00
2½"	2-7/8"	50'	DM25-50UC	268.00
2½"	2-7/8"	100'	DM25-100UC	537.00

Coupled with female and male NST (NH) thread, rocker lug, aluminum expansion ring couplings

Size	Bowl	Length	Part #	Price/E
1½"	1-13/16"	50'	DM15-50RAF	\$275.85
1½"	1-13/16"	100'	DM15100RAF	435.85
2½"	2-7/8"	50'	DM25-50RAF	376.70
2½"	2-7/8"	100'	DM25100RAF	647.55



Coupled with female and male NPSH thread, rocker lug, aluminum expansion ring couplings

Size	Bowl	Length	Part #	Price/E
1½"	1-13/16"	50'	DM15-50RAS	\$236.50
1½"	1-13/16"	100'	DM15100RAS	435.85
2"	2-5/16"	50'	DM20-50RAS	314.40
2"	2-5/16"	100'	DM20100RAS	480.25
2½"	2-7/8"	50'	DM25-50RAS	371.55
2½"	2-7/8"	100'	DM25100RAS	647.55

NEW

P



Coupled with male (NPT) x male (NPT) thread, rocker lug, aluminum expansion ring couplings

Size	Bowl	Length	Part #	Price/E
1½"	1-13/16"	50'	DM15-50RAT	\$296.75
1½"	1-13/16"	100'	DM15100RAT	435.85
2"	2-5/16"	50'	DM20-50RAT	372.50
2"	2-5/16"	100'	DM20100RAT	573.40
2½"	2-7/8"	50'	DM25-50RAT	434.30
2½"	2-7/8"	100'	DM25100RAT	663.00

- 75' lengths and other threads and configurations are available, consult Dixon™