Forestry Non Weeping Fire Hose

Features

- outer construction: single jacket, all polyester
- tube construction: thermoplastic
- impregnation: yellow
- proof pressure: 600 PSI at ambient temperature (70°F)
- service test pressure: **300 PSI** at ambient temperature (70°F)
- working pressure: 270 PSI at ambient temperature (70°F)
- consult Dixon™ for pricing and availability of 25' lengths, other threads and configurations

Coupled with female and male expansion ring couplings

Size	Length	Part #	Rocker Lug Aluminum <i>NST (NH</i>) RAF	Rocker Lug Aluminum NPSH RAS
1"	50'	NF610Y50		\$470.00
1"	100'	NF610Y100		517.20
1½"	50'	NF615Y50	\$372.85	372.85
1½"	100'	NF615Y100	625.00	625.00

Forestry Mop Up Hose

Application:

 used on mop-up and low volume hand lines, filling pump cans, supplying sprinklers and remote fire line protection

Features:

- 50' coil diameter is 9"
- · outer construction: single jacket, synthetic
- tube construction: thermoplastic
- impregnation: yellow
- proof pressure: **300 PSI** at ambient temperature (70°F)
- service test pressure: 150 PSI at ambient temperature (70°F)
- working pressure: 135 PSI at ambient temperature (70°F)
- consult Dixon™ for pricing and availability of other threads and configurations

Coupled with female and male brass ferrule type garden hose couplings

Size	Length	Part #	Price/E
3/4"	50'	NF307Y50GHT	\$221.25
1½"	50'	NF615-50RAQT1	360.85
1½"	100'	NF615100RAQT1	589.95

¹ coupled with quarter turn forestry couplings

Forestry Mop Up Hose Kit



Description	Part #	Price/E
kit contains: hose, pouch and nozzle	NF307Y50GHT-KIT	\$355.10