Strap-Grip Saddles and Fittings









Features:

- design provides greater resistance to end pull than conventional band clamps
- only the fittings shown below are designed for use with Strap-Grip Saddles
- saddles are sold in pairs and designed for use with 3/4" or 5/8" wide band clamps
- bands must be purchased separately
- band clamps should first be applied to the OD to seal the hose, then Strap-Grip saddles should be banded over the initial clamp to anchor the fitting in the hose

saddles only



saddles

0:	Hose OD		Plated Iron		
Size	from	to	Part #	Price/E 1	
1½"	1-13/16"	2-1/8"	SGS150	\$14.40	
2"	2-5/8"	3"	SGS200	17.35	
3"	3-1/2"	3-7/8"	SGS300	21.40	
4"	4-9/16"	5-1/8"	SGS400	24.40	
6"	6-1/2"	7-1/16"	SGS600	45.00	

¹ prices are for a two saddle set

male NPT x hose shank



male NPT x hose shank

Size	Schedule 40 Plated Carbon Steel		Schedule 40 Stainless Steel		Schedule 80¹ Plated Carbon Steel	
	Part #	Price/E	Part #	Price/E	Part #	Price/E
1½"	LP21	\$60.00			LP21-80	\$69.00
2"	LP26	53.20			LP26-80	71.85
3"	LP36	125.00	RLP36 ²	\$221.40		
4"	LP46	164.00	RLP46 ²	375.00		
6"	LP66	340.00				

- ¹ Schedule 80 stems meet NFPA 58 standard
- ² tubular steel construction

Boss-Lock™ type C coupler x hose shank



female coupler x hose shank

Size	316 Stainless			
	Part #	Price/E		
1"	RC100CEZ	\$120.20		
1½"	RC150CEZ	170.00		
2"	RC200CF7	152 25		