## Dixon<sup>™</sup> 4-Way Siamese

## Features:

- used to supply large diameter hose from multiple smaller lines, can be used to distribute water in the opposite direction
- lightweight and compact
- convenient carrying handle built on the body
- maximum operating pressure: 280 PSI at 70°F (21°C), without relief valve
- water way: 4 inlet side 21/2" maximum, 1 outlet 41/2" maximum
- finish anodized throughout (minimum thickness 0.001")
- FSSV siamese with clappers
  - MSSV wyes without clappers

SSV - customer to specify if clappered or not

Outlet Storz	(4) Inlets	<i>Alum. Alloy, 356-T6</i> Part #	Price	Length	Width	Height
4"	21/2" fem. swivel	FSSV4-425F	\$2417.40	13½"	18"	7½"
5"	21/2" fem. swivel	FSSV4-525F	2391.10	13½"	18"	8"
6"	21/2" fem. swivel	FSSV4-625F	2250.20	13½"	18"	8"
4"	21⁄2" male	MSSV4-425F	2222.10	12¾"	16¾"	7½"
5"	21⁄2" male	MSSV4-525F	2109.90	12¾"	16¾"	8"
6"	21⁄2" male	MSSV4-625F	2317.25	12¾"	16¾"	8"
4"	21/2" Storz	SSV4-425	2050.40	121⁄2"	17¼"	7½"
5"	21/2" Storz	SSV4-525	2000.80	12½"	17¼"	8"
6"	21/2" Storz	SSV4-625	2278.95	12½"	17¼"	81⁄2"

## **Dixon<sup>™</sup> Jumbo Siamese**

## Features:

- used to supply one large diameter hose from two large diameter hose lines, can be used to distribute water in the opposite direction
- hard coat anodized throughout
- maximum operating pressure: 280 PSI at 70°F (21°C), without relief valve
- water way: 2 inlet side 4" maximum, 1 outlet 41/2" maximum
- finish anodized throughout (minimum thickness 0.001")

Outlet Storz	(2) Inlets Storz	<i>Alum. Alloy, 356-T6</i> Part #	Price	Length	Width	Height
4"	4"	SSVJ440	\$2400.35	12½"	13¼"	6½"
5"	4"	SSVJ540	2400.35	12¾"	13¼"	8"
5"	5"	SSVJ550	2400.35	13¾"	13¼"	8"





Ρ