

Hand Hydrotest Pump



Application

- Designed for use in testing pipe lines, pressure tanks, and pressure vessels

Feature

- Uses check valves, which are more efficient and longer lasting than poppet systems

Material

- Stainless steel piston

Specifications

- Cylinder displacement: 1.37 cu. in.
- 0 -1000 PSI pressure gauge, 10' high pressure hose and quick disconnect coupler included
- Piston: 7/8" with 2" stroke
- Working pressure: 1000 PSI at 70°F (21°C)

NPT Inlet	NPT Outlet	Aluminum Part #
1/2"	1/2"	HHTP

Hydrostatic Test Pumps

Electric Test Pump



Features

- 110 volt Portable Hydrostatic Electric Pump - Model (ETP)
- Quick connect garden hose coupler for water supply line available

Specifications

- 3000 PSI maximum test pressure
- 1.3 GPM fill rate (at 60 PSI inlet water pressure)
- 1/2" x 25' intermediate hose with brass straight-thru quick coupler x NPSM swivel connection
- 1/2" brass straight-thru plug on pressure outlet
- 0 – 3000 PSI back mount liquid filled pressure gauge

Part #
ETP

Pneumatic Test Pump

Features

- Stainless interior
- Air gauge for quick, easy adjustment of maximum test pressure
- High pressure test gauge
- Filter/regulator for clean, dry air to ensure long life of unit
- On - off valve for air input
- 15' of hose included
- Easy to use: portable hand cart mount or stationary wall mount available
- Use of coalescing filter and water filter recommended for prolonged pump life

Specifications

- 5.5 GPM fill rate
- Test pressure: 0 to 1500 PSI

Hand Cart Mount Part #	Wall Mount Part #
PTP	PTP-WM