

## Wilkerson FRLs

### F28-Series Standard Airline Filters

**Features**

- High flow capacity
- 5 micron element
- 2.87 oz. bowl


**Specifications**

- Maximum operating conditions:
  - transparent bowl: 150 PSIG (10.3 bar) and -13°F to 125°F (-25°C to 52°C)
  - metal bowl: 250 PSIG (17.2 bar) and -13°F to 150°F (-25.5°C to 65.5°C)

| Size | Flow (SCFM) | Transparent Bowl and Guard |                     | Metal Bowl with Sight Glass |                     |
|------|-------------|----------------------------|---------------------|-----------------------------|---------------------|
|      |             | Automatic Drain Part #     | Manual Drain Part # | Automatic Drain Part #      | Manual Drain Part # |
| 3/8" | 115         | F28-03A                    | F28-03M             | F28-03AMB                   | F28-03MMB           |
| 1/2" | 120         | F28-04A                    | F28-04M             | F28-04AMB                   | F28-04MMB           |
| 3/4" | 145         | F28-06A                    | F28-06M             | F28-06AMB                   | F28-06MMB           |



Transparent bowl with guard



### F30-Series Jumbo Airline Filters

**Features**

- 5 micron element
- 2 oz. bowl


**Specifications**

- Maximum operating conditions:
  - transparent bowl: 150 PSIG (10.3 bar) and 32°F to 125°F (0°C to 52°C)
  - metal bowl: 200 PSIG (13.8 bar) and 32°F to 150°F (0°C to 65.5°C)

| Size | Flow (SCFM) | Transparent Bowl and Guard |                     | Metal Bowl with Sight Glass |                     |
|------|-------------|----------------------------|---------------------|-----------------------------|---------------------|
|      |             | Automatic Drain Part #     | Manual Drain Part # | Automatic Drain Part #      | Manual Drain Part # |
| 3/4" | 316         | F30-06A                    | F30-06M             | F30-06AMB                   | F30-06MMB           |
| 1"   | 323         | F30-08A                    | F30-08M             | F30-08AMB                   | F30-08MMB           |



With guard



### F35-Series Jumbo Airline Filters

**Features**

- 5 micron element
- 12.5 oz. bowl


**Specifications**

- Maximum operating conditions:
  - metal bowl: 150 PSIG (10.3 bar) and 32°F to 150°F (0°C to 65.5°C)

| Size   | Flow (SCFM) | Heavy Duty Metal Bowl  |                     |
|--------|-------------|------------------------|---------------------|
|        |             | Automatic Drain Part # | Manual Drain Part # |
| 1-1/2" | 1280        | F35-0BAMB              | F35-0BMMB           |
| 2"     | 1400        | F35-0CAMB              | F35-0CMMB           |



With metal bowl



NOTE: SCFM ratings at 150 PSIG inlet pressure.

See pages 312 - 316 for accessories.

FRLs are designed for air service only, unless otherwise indicated.

