


Adjust-A-Power Nozzle



Features

- Ideal for patio, auto and boat, driveway, and garden
- Produces 50% more power than twist nozzles
- Does not require a washer
- Leave nozzle in the open position when not in use
- Brass construction with stainless steel bearings

Specifications

- Maximum operating pressure: **100 PSI** (water only) at ambient temperature **70°F (21°C)**

| Thread Size | Brass Part # |
|-------------|--------------|
| 3/4" GHT | AAPN75GHT |

Constant Flow Nozzle Displays

Features

- Shatterproof and UV resistant polycarbonate withstands tough environmental conditions
- Seals used for true water shut off
- Easy twist spray pattern adjustment
- Sold in case quantity only (25 per case), with display

| Thread | 45° Spray GPM @ 100 PSI | Color | Global Part # |
|----------|-------------------------|-------|---------------|
| 3/4" GHT | 25.1 | green | FNB75GHT-GD |
| | 25.1 | clear | CNB75GHT-GD |



FNB75GHT-GD

CNB75GHT-GD

Constant Flow Nozzles with Bumper

Feature

- Can be used as a replacement nozzle in the display case FNB75GHT-GD

| Thread | 45° Spray GPM @ 100 PSI | Color | Plastic Part # |
|----------|-------------------------|-------|---------------------|
| 3/4" GHT | 8.0 | green | GNB75GHT (domestic) |
| | 25.1 | clear | CNB75GHT (global) |



GNB75GHT



CNB75GHT

Plain Hose Nozzles

Feature

- Finish: satin

Specification

- Maximum operating pressure: **100 PSI** (water only) at **70°F (21°C)**

| Size | Thread | Overall Length | Orifice | Replacement Gasket | Brass | |
|------|--------|----------------|---------|--------------------|-----------------|--------|
| | | | | | Previous Part # | Part # |
| 3/4" | GHT | 6" | 1/4" | KRW5 | 500SN6 | BN6 |

