Grease Whip Hose Assemblies

Application

For use with hand grease guns only

Specifications

- 1/8"-27 male NPT, solid base (0010260C)
- Working pressure: 3000 PSI

Features

- One piece crimp couplings
- Add "S" to order carbon steel strain relief spring option

Approval

 US manufactured 3/16" I.D. hose - exceeds SAE 100R1-AT



Assembly Length	Brass		Strain Relief	
	Previous Part #	Part #	Option	
8"	GWH-0800	GWH0800	GWH0800S	
12"	GWH-1200	GWH1200	GWH1200S	
12		GWH1200R ¹		
18"	GWH-1800	GWH1800	GWH1800S	
10		GWH1800R ¹		
24"	GWH-2400	GWH2400	GWH2400S	
36"	GWH-3600	GWH3600	GWH3600S	
48"	GWH-4800	GWH4800	GWH4800S	
60"	GWH-6000	GWH6000	GWH6000S	

¹ Retail packaging

Grease Whip Hose Fittings

Features

- 0010055C, 0010260C, and 0010860C are designed to be crimped to 3/16" I.D. hose
- GWHC and GWHC-FF mate with Zerk fittings on the coupler side

Grease Hose Couplers



Description	Zinc Plated Steel		Optional
Description	Previous Part #	Part	Qty
1/8"-27 female NPT thread, grease hose coupler with ball check - valved shutoff	GWH-C	GWHC	25
1/8"-27 female NPT thread, full flow grease hose coupler		GWHC-FF	25

NOTE: Add 'R' suffix to part number for retail pack option





December	Brass		Optional
Description	Previous Part # Part #		Qty
1/8"-27 male NPT thread, drilled and chamfered base	001-0055	0010055C	100

Male NPT Thread - Solid Base



Description	Brass		Optional
Description	Previous Part #	Part #	Qty
1/8"-27 male NPT thread, solid base	001-0260	0010260C	100

Female NPT Thread



Decembries	Brass		Optional Qty
Description	Previous Part # Part #		
1/8"-27 female NPT thread	001-0860	0010860C	100