

Type F Adapters x NPT

Adapter x Male NPT

B



356T6 aluminum



aluminum hard coat



brass



unplated malleable iron



plated malleable iron



316 stainless

| Size | 356T6 Aluminum Part # | Aluminum Hard Coat Part # | Brass Part # |
|-------------|--------------------------|------------------------------|-----------------|
| 1/2" | 50-F-AL | --- | 50-F-BR |
| 3/4" x 1/2" | 7550-F-AL | --- | 7550-F-BR |
| 3/4" | 75-F-AL | --- | 75-F-BR |
| 1" | 100-F-AL | --- | 100-F-BR |
| 1-1/4" | 125-F-AL | --- | 125-F-BR |
| 1-1/2" | 150-F-AL | 150-F-ALH | 150-F-BR |
| 2" | 200-F-AL | 200-F-ALH | 200-F-BR |
| 2-1/2" | 250-F-AL | --- | 250-F-BR |
| 3" | 300-F-AL | 300-F-ALH | 300-F-BR |
| 4" | 400-F-AL | 400-F-ALH | 400-F-BR |
| 5" | 500-F-AL | --- | --- |
| 6" | 600-F-AL | 600-F-ALH | 600-F-BR |
| 8" DIX | 800-F-AL ¹ | --- | --- |
| 8" BL | 801-F-AL ¹ | --- | --- |

¹ Dixon® and Boss-Lock cam & groove couplings do not interchange in the 8" size.

NOTE: Pressure rating is based on the seal of the mating part. See ratings on page 20.



| Size | Unplated Malleable Iron Part # | Plated Malleable Iron Part # | 316 Stainless Steel Part # |
|-------------|-----------------------------------|---------------------------------|-------------------------------|
| 1/2" | --- | --- | 50-F-SS |
| 3/4" x 1/2" | --- | --- | 7550-F-SS |
| 3/4" | --- | 75-F-PM | 75-F-SS |
| 1" | --- | 100-F-PM | 100-F-SS |
| 1-1/4" | --- | --- | 125-F-SS |
| 1-1/2" | 150-F-MI | 150-F-PM | 150-F-SS |
| 2" | 200-F-MI | 200-F-PM | 200-F-SS |
| 2-1/2" | --- | --- | 250-F-SS |
| 3" | 300-F-MI | 300-F-PM | 300-F-SS |
| 4" | 400-F-MI | 400-F-PM | 400-F-SS |
| 6" | --- | 600-F-PM | 600-F-SS |