The Right Connection®

Quick-Release Worm Gear Clamps

Size

· Screw design: 5/16" slotted hex head

Features

- Suggested installation torque 25-35 in. lbs., maximum recommended torque 50 in. lbs.
- · Parts showing package quantities are sold in package quantities only
- Torque ratings correspond to the torque rating of the screw of the clamp and are not an indication of the working pressure of any hose assembly installed with this clamp



Materials

- · Band and housing: 201-series stainless
- · Style LS Screw: plated hardened carbon steel
- Style LSS Screw: SAE 410-series stainless

Band Width	Hose O.D.		Style LS	Pkg	Style LSS	Pkg
	from	to	Part #	Qty	Part #	Qty
1/2"	1-1/2"	3-1/2"	LS48	10	LSS48	10
	1"	4"	LS56	10		
	2"	5"	LS72	10	LSS72	10
	2"	6"	LS88	10	LSS88	10
	3-1/2"	6-1/2"	LS96			
	2-7/8"	7"	LS104	10	LSS104	10
	1-3/4"	8-1/2"	LS128		LSS128	
	2"	10"	LS152			
	2"	12-1/4"	LS188		LSS188	
	10-3/16"	14"			LSS216	
	1-3/4"	16"			LSS248	
	1-7/8"	20"			LSS312	



style LSS

Worm Gear Make-A-Clamp Kits

Application

• A maintenance clamp system in a box; by simply cutting off a piece of banding from a continuous roll, you can make any size stainless steel worm-driven clamp from 2" diameter and up, perfect applications requiring for varying sized large clamps

Sizes

Band width: 1/2"Band thickness: .023"

· Screw design: 5/16" slotted hex head

Feature

Reusable

Materials

· Band and housing material: 300 stainless

· Screw material: 410 stainless

Contents	Stainless Steel Part # 4000	
mini kit: 8-1/2' band, 3 adjustable fasteners, 1 band splice		
kit with 100' band, 25 adjustable fasteners, 10 band splices	4001	
kit with 50' band, 10 adjustable fasteners, 5 band splices	4002	
box with 10 adjustable fasteners: priced per box	4004	
box with 100' band, 10 band splices	4005	
box with 50' band, 5 band splices	4006	
6" demonstrator kit with clamps	4007	
box with 10 band splices: priced per box	4008	



