

H-BOP Series Hydraulic Couplings

Application

- Designed specifically for blowout preventer systems on drilling rigs

Features


- Steel coupler sleeves are hardened to resist deformation and maximize service life
- Individually marked with the BOP series designation
- Interchangeable with ISO7241 Series B, Eaton/Hansen HKFR-Series, DNP HNV-BOP Series

Specification

- Pressure rating **5000 PSI** at **70°F (21°C)**

Approval


- Fire tested and Lloyd's certified to **1300°F (700°C)** in accordance with API 16D; certificate available upon request



Blowout Preventer Safety Female Couplers

| Body Size | Female Threads | Steel Part # | 316 Stainless Steel Part # |
|-----------|------------------|--------------|----------------------------|
| 3/8" | 3/8" - 18 NPTF | 3HF3-BOP | 3HF3-SS-BOP |
| 1/2" | 1/2" - 14 NPTF | 4HF4-BOP | 4HF4-SS-BOP |
| 3/4" | 3/4" - 14 NPTF | 6HF6-BOP | 6HF6-SS-BOP |
| 1" | 1" - 11-1/2 NPTF | 8HF8-BOP | 8HF8-SS-BOP |

K



Blowout Preventer Safety Female Plugs

| Body Size | Female Threads | Steel Part # | 316 Stainless Steel Part # |
|-----------|------------------|--------------|----------------------------|
| 3/8" | 3/8" - 18 NPTF | H3F3-BOP | H3F3-SS-BOP |
| 1/2" | 1/2" - 14 NPTF | H4F4-BOP | H4F4-SS-BOP |
| 3/4" | 3/4" - 14 NPTF | H6F6-BOP | H6F6-SS-BOP |
| 1" | 1" - 11-1/2 NPTF | H8F8-BOP | H8F8-SS-BOP |