

## Hydraulic Adapters - NPTF

### Male Pipe Tees

#### Specifications

- Reference SAE 140437
- Pressure rating at 70°F (21°C)



| Male<br>NPTF (3) | PSI  | Zinc Plated Steel<br>Part # |
|------------------|------|-----------------------------|
| 1/4"-18          | 5000 | 5600-4                      |
| 3/8"-18          | 4000 | 5600-6                      |
| 1/2"-14          | 3000 | 5600-8                      |
| 3/4"-14          | 2500 | 5600-12                     |
| 1"-11-1/2        | 2000 | 5600-16                     |

### Male x Female Pipe Tees

#### Specifications

- Reference SAE 140427
- Pressure rating at 70°F (21°C)



| Male<br>NPTF (2) | Female<br>NPTF | PSI  | Zinc Plated Steel<br>Part # |
|------------------|----------------|------|-----------------------------|
| 1/4"-18          | 1/4"-18        | 5000 | 5601-4                      |
| 3/8"-18          | 3/8"-18        | 4000 | 5601-6                      |
| 1/2"-14          | 1/2"-14        | 3000 | 5601-8                      |
| 3/4"-14          | 3/4"-14        | 2500 | 5601-12                     |
| 1"-11-1/2        | 1"-11-1/2      | 2000 | 5601-16                     |

### Female x Male Branch Tees

#### Specifications

- Reference SAE 140425
- Pressure rating at 70°F (21°C)



| Female<br>NPTF (2) | Male<br>NPTF | PSI  | Zinc Plated Steel<br>Part # |
|--------------------|--------------|------|-----------------------------|
| 1/4"-18            | 1/4"-18      | 5000 | 5604-4                      |
| 3/8"-18            | 3/8"-18      | 4000 | 5604-6                      |
| 1/2"-14            | 1/2"-14      | 3000 | 5604-8                      |
| 3/4"-14            | 3/4"-14      | 2500 | 5604-12                     |
| 1"-11-1/2          | 1"-11-1/2    | 2000 | 5604-16                     |

### Female Pipe Tees

#### Specifications

- Reference 140438
- Pressure rating at 70°F (21°C)



| Female<br>NPTF (3) | PSI  | Zinc Plated Steel<br>Part # |
|--------------------|------|-----------------------------|
| 1/4"-18            | 5000 | 5605-4                      |
| 3/8"-18            | 4000 | 5605-6                      |
| 1/2"-14            | 3000 | 5605-8                      |
| 3/4"-14            | 2500 | 5605-12                     |
| 1"-11-1/2          | 2000 | 5605-16                     |

### Male x Female Run Tees

#### Specifications

- Reference 140424
- Pressure rating at 70°F (21°C)



| Male<br>NPTF  | Female<br>NPTF (2) | PSI  | Zinc Plated Steel<br>Part # |
|---------------|--------------------|------|-----------------------------|
| 1/8"-27       | 1/8"-27            | 5000 | 5602-2                      |
| 1/4"-18       | 1/4"-18            | 5000 | 5602-4                      |
| 3/8"-18       | 3/8"-18            | 4000 | 5602-6                      |
| 1/2"-14       | 1/2"-14            | 3000 | 5602-8                      |
| 3/4"-14       | 3/4"-14            | 2500 | 5602-12                     |
| 1"-11-1/2     | 1"-11-1/2          | 2000 | 5602-16                     |
| 1-1/4"-11-1/2 | 1-1/4"-11-1/2      | 1150 | 5602-20                     |
| 1-1/2"-11-1/2 | 1-1/2"-11-1/2      | 1000 | 5602-24                     |