

## Red Plain Hose Nozzles

### Specification

- Maximum operating pressure: **100 PSI** (water only) at 70°F (21°C)

| Size   | Thread   | Length | Orifice | Polycarbonate Part # |
|--------|----------|--------|---------|----------------------|
| 1-1/2" | NPSH     | 10"    | 1/2"    | PN15                 |
|        | NST (NH) |        |         | PN15F                |



## UL Play Pipes with Tip

### Application

- Often required in hydrant houses by insurance underwriters

### Features

- Swivel handle, red marlin trim
- Comes standard with 1-1/8" orifice tip

### Specification

- Maximum operating pressure: **100 PSI** (water only) at 70°F (21°C)

### Approvals

- UL listed and Factory Mutual approved
- ULT male thread specification: 2-3/16" ODM x 12 TPI

| Size          | Female Thread | Male Thread | Overall Length | Brass Part # |
|---------------|---------------|-------------|----------------|--------------|
| 2-1/2"        | NST (NH)      | ULT         | 30"            | UPP250F      |
| playpipe only |               |             |                | UPP250F-SPEC |



## Tips

### Feature

- Finish: satin

### Specification

- Maximum operating pressure: **100 PSI** (water only) at 70°F (21°C)

### Approval

- ULT male thread specification: 2-3/16" ODM x 12 TPI

| Orifice | Cast Brass Part # |
|---------|-------------------|
| 1-1/8"  | UPPT              |
| 1-1/4"  | UPPT125           |
| 1-1/2"  | UPPT150           |
| 1-3/4"  | UPPT175           |



## Street Cleaning Nozzles

### Feature

- Welded fabrication

| Size | Connection | Aluminum Part # |
|------|------------|-----------------|
| 2"   | female cam | 200DBAL         |
| 3"   | female cam | 300DBAL         |

