

2-Piece Domestic Stainless Steel Ball Valves

Feature

- Blow-out proof stem

Materials

- 316 stainless ball and stem
- RPTFE seal
- Vinyl handle cover

Specifications

- Temperature range: -40°F to 400°F (-40°C to 204°C)
- Pressure rating: 1,000 PSI CWP
- Pressure rating: 150 PSI saturated steam
- Vacuum service to 29 inches Hg



Female NPT	Port	316 Stainless Steel Part #
1/4"	full	DSBV25
3/8"		DSBV38
1/2"		DSBV50
3/4"		DSBV75
1"		DSBV100
1-1/4"		DSBV125
1-1/2"		DSBV150
2"		DSBV200

Stainless Steel Ball Valves Full Port

Applications

- For use with water, oil, and gas

Feature

- Blow-out proof stem design

Materials

- 316 stainless steel ball and stem
- RPTFE seat, joint gasket, and thrust washer

Specifications

- Temperature range:
-20°F to 300°F (-29°C to 149°C) as long as the valve is run fully open/closed
- Pressure rating:
1/4" - 2" rated to 1000 PSI WOG (CWP)
2-1/2" - 3" rated to 800 PSI WOG (CWP)
100 PSI saturated steam



Female NPT	Port	316 Stainless Steel Part #
1/4"	full	SSBV25
3/8"		SSBV38
1/2"		SSBV50
3/4"		SSBV75
1"		SSBV100
1-1/4"		SSBV125
1-1/2"		SSBV150
2"		SSBV200
2-1/2"		SSBV250
3"		SSBV300