

## Full Port Ball Valves with Locking Handle

### Applications

- For use with water, oil, and gas

### Features

- Lockable
- Blow-out proof stem design
- Not recommended as a throttling valve


### Materials

- 316 stainless steel ball and stem
- RPTFE seat, joint gasket and thrust washer
- Plastic cover on handle

### Specifications

- Temperature range: **-20°F to 356°F (-29°C to 180°C)**
- Pressure rating: 1/4" - 2" rated to **1000 PSI WOG (CWP)**  
2-1/2" - 3" rated to **800 PSI WOG (CWP)**  
**100 PSI saturated steam**

| Female NPT | Port | 316 Stainless Steel Part # |
|------------|------|----------------------------|
| 1/4"       | full | SSLBV25                    |
| 3/8"       |      | SSLBV38                    |
| 1/2"       |      | SSLBV50                    |
| 3/4"       |      | SSLBV75                    |
| 1"         |      | SSLBV100                   |
| 1-1/4"     |      | SSLBV125                   |
| 1-1/2"     |      | SSLBV150                   |
| 2"         |      | SSLBV200                   |
| 2-1/2"     |      | SSLBV250                   |
| 3"         |      | SSLBV300                   |



## Reduced Port Ball Valves with Locking Handle

### Applications

- For use with water, oil, and gas

### Features

- Lockable
- Blow-out proof stem design
- Not recommended as a throttling valve

### Materials

- 316 stainless steel ball and stem
- RPTFE seat, joint gasket, and thrust washer
- Plastic cover on handle

### Specifications

- Temperature range: **-20°F to 356°F (-29°C to 180°C)**
- Pressure rating: **1000 PSI WOG; 100 PSI saturated steam**

| Female NPT | Port    | 316 Stainless Steel Part # |
|------------|---------|----------------------------|
| 1/4"       | reduced | SSLBV25SP                  |
| 3/8"       |         | SSLBV38SP                  |
| 1/2"       |         | SSLBV50SP                  |
| 3/4"       |         | SSLBV75SP                  |
| 1"         |         | SSLBV100SP                 |
| 1-1/4"     |         | SSLBV125SP                 |
| 1-1/2"     |         | SSLBV150SP                 |
| 2"         |         | SSLBV200SP                 |

