


A B














Flange Adapters - Series-FA

Application

• Used to connect an ANSI Class 125 and 150 flange to a grooved pipe using a grooved clamp

Feature

 Provides a rigid one-piece connection that can be disconnected by removing the clamp assembly, o assemble to another flange, position bolt heads on the adapter (grooved) side

Material

Ductile iron body with rust inhibiting paint

Nominal	Pipe O.D.	Maximum Working Pressure	Flange Dimensions		Bolts		Ductile Iron
Size		PSI at 70°F (21°C)	Α	В	Qty	size	Part #
2"	2.375"	300	6"	2-3/8"	4	5/8"	FA20
3"	3.500"	300	7-1/4"	2-3/8"	4	5/8"	FA30
4"	4.500"	300	8-1/2"	2-3/8"	8	5/8"	FA40
6"	6.625"	300	11"	2-9/16"	8	3/4"	FA60
8"	8.625"	300	13-1/4"	3"	8	3/4"	FA80

ANSI Split Flanges - Series-SF

Application

 Provides a direct connection between a grooved adapter and an ANSI Class 125 and 150 raised face flanged component

Features

- Can be used with flat face flanges by removing the raised projections on the outside face of the flange
- Nitrile rubber gaskets are available upon request

Material

Ductile iron body with rust inhibiting paint

Approvals

 UL Listed and Factory Mutual approved

Comparable to

- Victaulic's #741
- Grinnell's #7012

Nom. Pipe Size O.D.	Pipe	Max. Work.	Flange Dims.		Bolts		Ductile Iron	Replacement
	Press. PSI at 70°F (21°C)	A	В	qty	size	with Gasket Part #1	EPDM Gaskets Part #2	
2"	2.375"	300	6"	13/16"	4	5/8"	ANSI20	FLG200E
2-1/2"	2.875"	300	7"	13/16"	4	5/8"	ANSI25	FLG250E
3"	3.500"	300	7-1/2"	13/16"	4	5/8"	ANSI30	FLG300E
4"	4.500"	300	9"	15/16"	8	5/8"	ANSI40	FLG400E
6"	6.625"	300	11"	1"	8	3/4"	ANSI60	FLG600E
8"	8.625"	300	13-1/2"	1-1/8"	8	3/4"	ANSI80	FLG800E

- 1 With EPDM gasket
- ² Replacement gasket

Reducing Adapters - Series-RA

Materia

Ductile iron body with rust inhibiting paint

Comparable to

- Victaulic's #50
- Grinnell's #7072

Approvals

UL listed and Factory Mutual approved

Nominal Size	Nominal Size	Dimensions E to E	Ductile Iron Part #		
2"	1-1/2"	2.5"	RAGG20150		
2-1/2"	2"	2.5"	RAGG25020		
3"	2"	2.5"	RAGG3020		
3	2-1/2"	2.5"	RAGG30250		
	2"	3.0"	RAGG4020		
4"	2-1/2"	3.0"	RAGG40250		
	3"	3.0"	RAGG4030		
5"	4"	3.5"	RAGG5040		
	2"	4.0"	RAGG6020		
6"	2-1/2"	4.0"	RAGG60250		
U	3"	4.0"	RAGG6030		
	4"	4.0"	RAGG6040		