

## High Density Polyethylene (HDPE) Couplings

### Applications

- Designed for mechanically joining high density polyethylene pipe and fittings

### Feature

- Uses four bolts to drive the sharply machined housing teeth into the outside of the pipe

### Material

- Ductile iron body with rust inhibiting paint

### Comparable to

- Grinnell's #9095

| Nominal Size | Pipe O.D. | Bolts |      |        | Ductile Iron               |                                      |
|--------------|-----------|-------|------|--------|----------------------------|--------------------------------------|
|              |           | qty   | size | length | Part #<br>with EPDM gasket | Part #<br>with Nitrile Rubber gasket |
| 2"           | 2.375"    | 4     | 1/2" | 2-3/8" | HDPE200                    | HDPE200BU                            |
| 3"           | 3.500"    | 4     | 1/2" | 3"     | HDPE300                    | HDPE300BU                            |
| 4"           | 4.500"    | 4     | 1/2" | 3"     | HDPE400                    | HDPE400BU                            |
| 6"           | 6.625"    | 4     | 5/8" | 3-1/2" | HDPE600                    | HDPE600BU                            |

### Dimensions

| A      | B      | C      |
|--------|--------|--------|
| 3-3/8" | 5-1/2" | 4-5/8" |
| 4-5/8" | 6-3/4" | 4-5/8" |
| 5-1/4" | 8"     | 5-3/4" |
| 7-1/2" | 11"    | 5-7/8" |

