

Air King®

**⚠ WARNING**

- The use of an Air King safety clip or wire type retainer is necessary to ensure Air King universal couplings will not become accidentally disconnected. This guarantees the fittings are properly connected because the safety pin will not go through the holes in mating flanges until couplings are locked in place. Only one Air King safety clip or wire type retainer is required for each Air King universal coupling.

**Feature**


- Supplied with safety clip and rubber washers, part # AWR4

**Specification**

- Pressure rating: **150 PSI** at ambient temperature **70°F (21°C)**

**Approval**

- Meets pressure requirements as specified in A-A-59553 commercial item description superseding Mil Spec.WWC-633D




**2-Lug Male NPT Ends**

| Size | Required Case Qty | Iron Part # |
|------|-------------------|-------------|
| 3/4" | 6                 | AM7         |



**2-Lug Female NPT Ends**

| Size | Required Case Qty | Iron Part # |
|------|-------------------|-------------|
| 3/4" | 6                 | AM8         |



**2-Lug Hose Ends**

| Size | Required Case Qty | Iron Part # |
|------|-------------------|-------------|
| 3/4" | 6                 | AM6         |

**Air King Clamps**

**Application**

- For use with Air King ends above

**Feature**

- Torque values for clamps are based on dry bolts. The use of lubricant on bolts will adversely effect clamp performance



| Hose ID | Hose OD |          | Required Case Qty | Torque ft. lbs. | Plated Iron Part # |
|---------|---------|----------|-------------------|-----------------|--------------------|
|         | from    | to       |                   |                 |                    |
| 3/4"    | 1-8/64" | 1-20/64" | 6                 | 21              | A9 <sup>1</sup>    |

<sup>1</sup> Global investment cast carbon steel

NOTE: Products placed in blue plastic bin with label.