FIoMAX Diesel Fueling System

Application

• Designed for on-site refueling of construction, mining, forestry, and agricultural equipment

Diesel Fuel Nozzles

- Features1-1/2" female NPT
- Tested to 180 gallons per minute
- Integrated high-flow swivel and sealing plug
- Plug/bumper assembly gives complete nose seal
- Investment cast aluminum housing
- Anodized aluminum non-wear parts
- Stainless steel wear components
- Delron[®] bushings eliminate metal-to-metal wear
- Interchanges with Caterpillar[®] and Wiggins systems

DescriptionPart #dog latch mechanism with sealing plugFN600ball lock with sealing plugFN600BLsealing plug for FN600FN600B-PLUGsealing plug for FN600BLFN600B

One-Piece Diesel Fuel Receivers

- Features
- 2" male NPT
- O-ring sealed aluminum cap
- Cap has set screw attached vinyl coated cable lanyard

Description	Material	Part #
one-piece receiver without cap	nickel-plated steel	FRS
one-piece receiver with cap	nickel-plated steel	FRS-C
one-piece receiver without cap	anodized aluminum	FRA
one-piece receiver with cap	anodized aluminum	FRA-C
cap for receiver	anodized aluminum	FR-CAP

Two-Piece Diesel Fuel Receivers

Features

- 2" male NPT
- O-ring sealed aluminum cap
- · Cap has set screw attached vinyl coated cable lanyard

Description	Part #
two-piece receiver with removable stainless sleeve, without cap	FR-RS
two-piece receiver with removable stainless sleeve with cap	FR-RS-C
removable sleeve replacement for two-piece receiver	FR-RS-R
cap for receiver	FR-CAP





