Air King® Accessories

Features

- The use of an Air King safety clip or wire type retainer is necessary to ensure couplings will
 not become accidentally disconnected, this guarantees the fittings are properly connected
 as the pin will not go through the holes in the mating flanges until couplings are locked
 in place
- Only one Air King safety clip or wire type retainer is required for each Air King universal coupling
- · Sold in package quantities only

Standard Safety Clip

Feature

· Same size clip can be used for all coupling sizes

Wire Diameter	Part #	Pkg Qty
.080	AC1	25

Safety Pins

Feature

· Heavy duty, oversized



Wire Diameter	Part #
.058	AKSP1
.091	AKSP25

Synthetic Lanyard

Features

- Synthetic cord
- · Same size for all coupling sizes

Part #	Pkg Qty
ACL8	25

2-Lug Washers

Features

- · 2-lug couplings use the same size washer, part number's AWR4, AWS6
- · Neoprene is oil resistant

Specifications

- Rubber temperature range: -20°F to 160°F (-29°C to 71°C)
- Neoprene temperature range: -20°F to 190°F (-29°C to 88°C)

Style	Rubber Part #	Neoprene Part #	Pkg Qty
2 lug	AWR4 ¹	AWS6	50

¹ Made from styrene-butadiene (SBR)

4-Lug Washer

Features

· 4-lug couplings use the same size washer, part number AWR14

Specifications

• Rubber temperature range: -20°F to 160°F (-29°C to 71°C)

Style	Rubber Part #
4 lug	AWR14



AWR4



AWS6



