

NK-Series Japanese Pneumatic Couplings

- Features
- Japanese Industrial Interchange Pneumatic Coupling
 - Interchanges with Nitto Kohki Hi-Cupla 200, Rectus Series 13, and CEJN Series 315

- Specifications
- Nitrile rubber seals are standard temperature range -40°F to 250°F (-40°C to 121°C)
 - Pressure rating: 300 PSI

Female Threaded Plugs

Body Size	Threads	Steel Part #
1/4"	1/4" - 18 NPT	NK2F2
	1/4" -19 BSPP	NK2BF2

Male Threaded Plugs

Body Size	Threads	Steel Part #
1/4"	1/4" - 18 NPT	NK2M2
	1/4" -19 BSPP	NK2BM2

Hose Barb Plug

Body Size	Hose I.D.	Steel Part #
1/4"	1/4"	NK2S2

Female Threaded Couplers

Body Size	Threads	Steel Part #
1/4"	1/4" - 18 NPT	2NKF2
	1/4" -19 BSPP	2NKBF2

Male Threaded Couplers

Body Size	Threads	Steel Part #
1/4"	1/4" - 18 NPT	2NKM2
	1/4" -19 BSPP	2NKBM2

Hose Barb Coupler

Body Size	Hose I.D.	Steel Part #
1/4"	1/4"	2NKS2