

Safety Cables261 - 263

King Cable®	261
Nylon safety restraints	262
King safety whipsnocks	263
King safety shackles	263
ASME air receiver manifold with King safety whipsnocks	263

Air Tanks and Manifolds 264 - 267

ASME air receiver manifolds	264 - 265
Whip hose assemblies	265
Manifolds	266 - 267
Compressor Y	267
Lubricants	267

In-Line Lubricators and Filters268 - 269

Lubricators	268
Air filter	268
Nipple filters	269
Lubricator with filter	269
Mini lubricators	269

Valves, Mufflers, and Vents.....270 - 276

Safety check valves	270
Conical mufflers	271
Speed control mufflers	271
Breather vents	271
Quiet flow economy pneumatic silencers/mufflers	272
Keychain	272
Mini in-line filter	272
General purpose regulators	272
Needle valves	273
Desiccant dryer	273
Button and tank filler valves	274
Brass lever external drains	274
Brass external drain cocks	274
Safety pop-off valves	275
Flow control valves	276
Series C check valves	276

Blow guns277 - 281

Safety	277 - 278
Pistol Grip	278
Non-Safety	278 - 279
Heavy duty	280
High volume	280 - 281

Air Hose.....282 - 283

Coil-Chief self-storing	282
Polyurethane	282 - 283
Industrial coupler blow gun	283

Tire pressure gauges..... 284**Swivels 285**

Ball	285
In-line	285
Air tool	285

Hose Reels.....286 - 287

Reelcraft®	286 - 287
5000-Series	286
7000-Series	286
80000 Series	287
30000 manual driven	287

FRLs288 - 338

Wilkerson	288 - 316
Miniatures	288 - 291
Filters	292 - 296
Manual in-line desiccant dryer	297
Regulators	297 - 301
Filter / regulator	302 - 303
Lubricators	303 - 306
Combination units	306 - 310
Exhaust mufflers	310
Automatic drains	311
Lockout valves	311
Accessories and repair kits	312 - 316
Series 1	317 - 337
Miniatures	317 - 319
Filters	319 - 322
Regulators	323 - 326
Filter / regulators	326 - 328
Lubricators	328 - 331
Combination units	332
Automatic drains	333
Accessories and repair kits	333 - 338

⚠ WARNING

The constant vibration created by air tools, like air drills and pavement breakers, is destructive to air hose couplings, especially the quick-acting type. To provide protection against coupling breakage and related hazards, Dixon® recommends the use of a whip hose. To construct a whip hose, connect one end of a short (3' to 10') air hose to the air tool using a 3500 type steel nipple. Connect the other end of the hose to the air supply using the standard quick-acting coupling. The heat-treated 3500 nipple will withstand vibration far better than the standard coupling and provide a safer connection. The whip hose should remain permanently connected to the tool.