

Push-On Hose Barb Fittings

Assembly Instructions

1. Trim hose end with smooth square cut
2. Lubricate either push-on fitting, hose, or both.
3. Insert push-on fitting into hose until first barb is in hose.
4. Place end of fitting against a flat object (bench, wall, etc.) and grip the hose one inch from end. Push with a steady force until end of hose is covered by yellow plastic cap.


Disassembly Instructions

1. Leaving push-on fitting in place, make a 1" cut in the hose along the barbed end of the fitting. Note: Be careful not to nick barbs when cutting the hose.
  2. With firm grip on hose, give a sharp downward pull to release the fitting from the hose.
- Intended for use with Lok-On (push-on style) hose only
  - No hose clamps or ferrules are needed for installation
  - Properly grips push-on hose only when pushed all the way in, with the cut end of the hose completely concealed by the plastic cap.



Male NPTF x Hose Barb


| Hose I.D. | Male NPTF | Brass           |                       |         | Brass Cap Option |         | Lead-Free Brass <sup>1</sup> | Pkg Qty |
|-----------|-----------|-----------------|-----------------------|---------|------------------|---------|------------------------------|---------|
|           |           | Previous Part # | Part #                | Pkg Qty | Part #           | Pkg Qty | Part #                       |         |
| 1/4"      | 1/8"      | BPN21           | 2720402C              | 100     | 2720402CBC       | 100     | 2720402CLF                   | 100     |
|           | 1/4"      | BPN22           | 2720404C              | 100     | 2720404CBC       | 100     | 2720404CLF                   | 100     |
|           | 3/8"      | BPN23           | 2720406C              | 50      | 2720406CBC       | 50      | ---                          | ---     |
| 5/16"     | 1/8"      | BPN251          | 2720502C              | 100     | ---              | ---     | ---                          | ---     |
|           | 1/4"      | BPN252          | 2720504C              | 50      | ---              | ---     | ---                          | ---     |
| 3/8"      | 1/8"      | BPN31           | 2720602C              | 100     | 2720602CBC       | 100     | ---                          | ---     |
|           | 1/4"      | BPN32           | 2720604C              | 50      | 2720604CBC       | 50      | 2720604CLF                   | 50      |
|           | 3/8"      | BPN33           | 2720606C              | 50      | 2720606CBC       | 50      | 2720606CLF                   | 50      |
|           | 1/2"      | BPN34           | 2720608C              | 25      | 2720608CBC       | 25      | ---                          | ---     |
|           | 3/4"      | BPN36           | 2720612C              | 25      | 2720612CBC       | 25      | ---                          | ---     |
| 1/2"      | 1/4"      | BPN42           | 2720804C              | 25      | 2720804CBC       | 25      | ---                          | ---     |
|           | 3/8"      | BPN43           | 2720806C              | 25      | 2720806CBC       | 25      | 2720806CLF                   | 50      |
|           | 1/2"      | BPN44           | 2720808C              | 50      | 2720808CBC       | 50      | 2720808CLF                   | 25      |
| 5/8"      | 3/4"      | BPN46           | 2720812C              | 50      | 2720812CBC       | 50      | ---                          | ---     |
|           | 3/8"      | BPN53           | 2721006C              | 25      | 2721006CBC       | 25      | ---                          | ---     |
|           | 1/2"      | BPN54           | 2721008C              | 25      | 2721008CBC       | 25      | ---                          | ---     |
| 3/4"      | 3/4"      | BPN56           | 2721012C              | 25      | 2721012CBC       | 25      | ---                          | ---     |
|           | 1/2"      | BPN64           | 2721208C              | 25      | 2721208CBC       | 25      | ---                          | ---     |
|           | 3/4"      | BPN66           | 2721212C              | 25      | 2721212CBC       | 25      | ---                          | ---     |
| 1"        | 3/4"      | BPN86           | 2721612C              | 10      | ---              | ---     | ---                          | ---     |
|           | 1"        | BPN88           | 2721616C <sup>2</sup> | 10      | ---              | ---     | ---                          | ---     |



brass



brass cap



303 stainless steel

| Hose I.D. | Male NPT | 303 Stainless Steel |                        | Pkg Qty |
|-----------|----------|---------------------|------------------------|---------|
|           |          | Previous Part #     | Part #                 |         |
| 1/4"      | 1/8"     | RPN21               | 2720402SS              | 100     |
|           | 1/4"     | RPN22               | 2720404SS              | 100     |
| 3/8"      | 1/4"     | RPN32               | 2720604SS              | 50      |
|           | 3/8"     | RPN33               | 2720606SS              | 50      |
| 1/2"      | 1/4"     | RPN42               | 2720804SS              | 25      |
|           | 3/8"     | RPN43               | 2720806SS              | 50      |
|           | 1/2"     | RPN44               | 2720808SS              | 25      |
| 3/4"      | 1/2"     | RPN64               | 2721208SS              | 25      |
|           | 3/4"     | RPN66               | 2721212SS              | 20      |
| 1"        | 1"       | RPN88               | 2721616SS <sup>2</sup> | 5       |

<sup>1</sup> NSF®/ANSI 61 certified Lead-Free Brass <=0.25% lead, Alloy C2745

<sup>2</sup> Capped

NOTE: Refer to page 441 for push-on garden hose thread fittings

NOTE: Optional package quantity

Male NPTF Swivel x Hose Barb

| Hose I.D. | Male NPTF | Brass           |          | Pkg Qty |
|-----------|-----------|-----------------|----------|---------|
|           |           | Previous Part # | Part #   |         |
| 1/4"      | 1/8"      | 271-0402        | 2710402C | 100     |
|           | 1/4"      | 271-0404        | 2710404C | 50      |
| 3/8"      | 1/4"      | 271-0604        | 2710604C | 50      |
|           | 3/8"      | 271-0606        | 2710606C | 50      |
| 1/2"      | 3/8"      | 271-0806        | 2710806C | 25      |
|           | 1/2"      | 271-0808        | 2710808C | 20      |
| 3/4"      | 3/4"      | 271-1212        | 2711212C | 10      |

NOTE: Swivel for assembly convenience only, not for live swivel applications; operational PSI is 80