

B



swaged assembly



crimped assembly



Type E Adapters with Swaged Ferrule

Application

- Developed specifically for chemical transport hoses having Crosslinked Polyethylene (XLPE) or Ultra High Molecular Weight Polyethylene (UHMW) tubes.

Features

- Provides a permanently attached cam & groove fitting when superior coupling retention is required
- Testing tank transport hoses from a wide variety of manufacturers proved the swaged Boss-Lock fitting to be the leader in overall performance
- Other sizes or hose O.D.s available on special order. Consult Dixon® for pricing and availability
- Special equipment required for installation, consult Dixon for pricing and availability or refer to page 572 for more information

| Size | Hose O.D. | | 316 Stainless Steel Part # |
|------|-----------|----------|----------------------------|
| | from | to | |
| 3/4" | 1-6/64" | 1-22/64" | RE075-1370 |
| 1" | 1-29/64" | 1-35/64" | RE100-1620 |
| 1" | 1-36/64" | 1-44/64" | RE100-1770 |

Type E Adapters with Notched Shank

Adapter x Hose Shank

Features

- Can be removed from a damaged hose by cutting away the ferrule without necessarily damaging the fitting, after inspection of the fitting to determine its suitability for reuse, it can be reinstalled into another hose by using a new ferrule
- System allows you to better manage your inventory: stock one coupling and two ferrules and cover the same hose range with less inventory, you must purchase a fitting and the matching ferrule to create an assembly
- For use with notched ferrules below

Dixon stems and ferrules are specifically designed to be used together as a coupling system. Due to differences in dimensions and tolerances for safety reasons, do not use other manufacturers' stems or ferrules with Dixon products. 

| Size | 316 Stainless Steel Part # |
|--------|----------------------------|
| 1-1/2" | RE150NO |
| 2" | RE200NO |
| 3" | RE300NO |
| 4" | RE400NO |

Notched Ferrules

- Reference notched shanks and adapters above
- Dixon stems and ferrules are specifically designed to be used together as a coupling system, due to differences in dimensions and tolerances for safety reasons, do not use other manufacturers' stems or ferrules with Holedall® products. 

| Size | Hose O.D. | | 304 Stainless Steel Part # |
|--------|-----------|----------|----------------------------|
| | From | To | |
| 1-1/2" | 1-60/64" | 2-12/64" | GAS2334NO |
| | 2-4/64" | 2-22/64" | GAS2370NO |
| 2" | 2-30/64" | 2-44/64" | GAS2709NO |
| | 2-42/64" | 2-54/64" | GAS2885NO |
| 2-1/2" | 2-54/64" | 3" | GAS3012NO |
| | 3-1/64" | 3-13/64" | GAS3260NO |
| 3" | 3-30/64" | 3-46/64" | GAS3760NO |
| | 3-47/64" | 3-54/64" | GAS3885NO |
| 4" | 4-40/64" | 4-47/64" | GAS5010NO |