

Pipe Fittings

NPT Threaded Square Head Plugs

Feature

- Brass plugs are solid
- Lead-Free Brass per NSF/ANSI 372

Male NPF- SAE	Lead-Free Brass 260/270 Part #
1/8"	2110200C
1/4"	2110400C
3/8"	2110600C
1/2"	2110800C
3/4"	2111200C



Hex Head Plugs

NPT	Brass		Pkg Qty	Lead-Free Brass ^{1,2} Part #
	Previous Part #	Part #		
1/8"	HHP1M	1630200C	50	1630200CLF
1/4"	HHP2M	1630400C	100	1630400CLF
3/8"	HHP3M	1630600C	25	---
1/2"	HHP4M	1630800C	25	---
3/4"	HHP6M	1631200C	25	---
1"	HHP8M	1631600C	10	---



¹ Lead-free brass <=0.25% lead; Alloy CA2745; Alloy C46400

² Conforms To: Safe Water Drinking Act (SWDA) of Jan. 4, 2014; California AB1953; RoHS Compliant

NOTE: Standard brass hex head plug is hollow; lead-free brass is solid

Hex Socket Plugs

Feature

- Lead-free brass per NSF/ANSI 372

NPTF	Lead-Free Brass 260/270		Optional Qty
	Previous Part #	Part #	
1/8"	219-0200	2190200C	50
1/4"	219-0400	2190400C	100
3/8"	219-0600	2190600C	25
1/2"	219-0800	2190800C	25
3/4"	219-1200	2191200C	25



NOTE: For additional information on pipe dimensions please reference dixonvalve.com.

LockNLube[®] Grease Coupler

Application

- Fits all DIN and SAE specification Zerk fittings (grease nipples)

Features

- Works on all grease fittings, SAE, and metric
- Works with all grease gun types - pneumatic, manual, and electric
- Lock-on mechanism - four hardened steel jaws are resilient under high pressure
- Will not leak once locked on, grease goes in the machine and will clear most clogged fittings
- Hands-free, does not release under pressure
- Easy release thumb lever disconnects with ease
- Free rebuild kit included with every LockNLube grease coupler

Material

- Seal - durable nitrile seal for longevity under high pressure

Specification

- Rated up to **10,000 PSI**



Size	Length	Width	Height	Diameter (Front Coupler)	Part #
1/8" NPT	3-1/2"	5/8"	1-7/8"	5/8"	LLGC18