Non-collapsible Hose

Chemical Booster Hose - Red

Size

- 3/4" diameter hose is coupled with 1" threaded couplings

Feature

 Reinforced with multiple plies of high tensile Aramid yarn providing flexible strength

Materials

- Outer cover material: specially compounded red EPDM tough cover
- Inner tube material: smooth black synthetic EPDM rubber

Coupled with female and male NST (NH) thread, chromed brass hole type couplings

Size	Length	Part #
3/4"	50'	80B07-50HCF
	100'	80B07-100HCF
]"	50'	80B10-50HCF
	100'	80B10-100HCF

Coupled with female and male NST (NH) thread, hole type coupling, aluminum expansion ring couplings

Size	Length	Part #
3/4"	50'	80B07-50HAF
	100'	80B07-100HAF
1"	50'	80B10-50HAF
	100'	80B10-100HAF

Fire and Utility Hose - Red

Features

- Outer construction is designed to withstand abrasion
- Consult Dixon[®] for pricing and availability of other lengths, threads, and configurations
- · Also available with chrome brass fittings

Specifications

Specification

Approval

• Working pressure: 800 PSI

Meets and exceeds NFPA standard 1961

- Working pressure: 200 PSI at ambient temperature 70°F (21°C)
- · Burst pressure: 600 PSI at ambient temperature 70°F (21°C)

Coupled with female and male NST (NH) thread, rocker lug, brass expansion ring couplings



Size	Length	Part #
1-1/2"	50'	15B15-50RBF
1-1/2	100'	15B15-100RBF

Coupled with female and male NST (NH) thread, rocker lug, aluminum expansion ring couplings

	Size	Length	Part #
	1-1/2"	50'	15B15-50RAF
		100'	15B15-100RAF

Coupled with female and male NPSH thread, rocker lug, aluminum expansion ring couplings

An and the second	Size	Length	Part #
	1-1/2"	50'	15B15-50RAS
		100'	15B15-100RAS



877 963 1966	•	dixonvalve.com
011.303.4300		uixonvaive.com

