Fire Hose, Fittings, and Accessories



Steel Hose Cabinet

Features

- · Designed for wall installation, with or without legs, or free standing
- Supplied with holes in the back for wall mounting and 1" pipe couplings on the bottom for adding legs
- Hose, accessories, and mounting hardware not included
- Furnished without legs; if legs are required, contact Dixon®

Material

• Red polyester coated finish on 18-gauge steel

Approval

Factory Mutual approved



Steel Part #	
HC30143	

Dimensions

Width	Depth	Height
60"	15"	48"

Basic Approved Equipment for Hose Cabinet

Examples		Quantity Required			
Part #	Description	Page #	Factory Mutual	UL & FIA	ISC
A525-50RAF ¹	2-1/2" x 50' single jacket hose	752	4	5	5
A515-50RAF ¹	1-1/2" x 50' single jacket hose	752	2	0	0
UPP250F1	Underwriters play pipe	783	0	2	2
BFN250NST ¹	2-1/2" adjustable fog nozzle	780	2	0	0
BFN150NST ¹	1-1/2" adjustable fog nozzle	780	1	0	0
HA2515F1	2-1/2" x 1-1/2" pin lug adapter	800	1	0	0
233	universal spanner	828	4	5	5
189	adjustable hydrant wrench	829	2	2	2
PHFA6	6 lb. fire axe	851	0	1	1
FCB48	crowbar		0	1	1
SW1501	1-1/2" hose coupling gasket	767, 768, 782, 814	4	5	5
SW2501	2-1/2" hose coupling gasket	767, 768, 782, 814, 821	2	0	0

¹ Threads must be appropriate to the authority having jurisdiction