

Viper® Select Gallonage Nozzle

Feature

• Four gallonage selection rings 30, 60, 90, and 125 GPM



Materials

• Constructed of E-Lite® aluminum and brass internals

Specification

• Maximum working pressure 100 PSI

Size	Thread	GPM @ 100 PSI	Part #
1-1/2"	NST	30 - 125	DSG3012F
	NPSH		DSG3012S



Feature

• Four gallonage selection rings 15, 30, 50, and 60 GPM

Size	Thread	GPM @ 100 PSI	Part #
1-1/2"	NST	15 - 60	DSG1560F
	NPSH		DSG1560S



Viper Select Gallonage Low Flow Nozzle

Features

- Four gallonage selection rings 5, 10, 25, and 40 GPM
- · Available without pistol grip



Materials

· Constructed of E-Lite aluminum and brass internals

Specification

Maximum working pressure 100 PSI

Size	Thread	GPM @ 100 PSI	Part #
1"	NST	5 - 40	DSG540F
	NPSH		DSG540S



Viper Constant Gallonage Nozzle

Features

- · Fulltime swivels and spinning teeth
- · BIMATIC flush system allows flush without shutting down
- · Removable pistol grip



Materials

· Constructed of E-Lite aluminum and brass internals

Specification

· Maximum working pressure 100 PSI



Size	Thread	GPM @ 100 PSI	Part #
1-1/2"	NST	60 - 95	DCG2510F
	NPSH		DCG2510S
2-1/2"	NST	150 - 200	DCG8020F
	NPSH		DCG8020S