

## Type E Adapters

### Adapter x Hose Shank

B



#### Features

- 1/2" couplers and adapters will interchange with 3/4" couplers and adapters, only the threads and barbs are 1/2"
- 1-1/4" couplers and adapters will interchange with 1-1/2" couplers and adapters, only the threads and barbs are 1-1/4"
- NOT recommended for use with PTFE gaskets, polypropylene cam & groove should not be mixed with metal fittings



#### Specification

- Maximum operating pressure: **125 PSI** (1/2" - 1"), **100 PSI** (1-1/4" - 2"), **60 PSI** (3"), and **50 PSI** (4"); recommendations based on the use of mating Dixon® fittings at an ambient temperature of **70°F (21°C)** with standard seal installed

| Size            | Glass-Filled Polypropylene<br>Part # | Optional Qty |
|-----------------|--------------------------------------|--------------|
| 3/4" x 1/2"     | PPE50                                | 24           |
| 3/4"            | PPE75                                | 24           |
| 1"              | PPE100                               | 24           |
| 1-1/2" x 1-1/4" | PPE125                               | 24           |
| 1-1/2"          | PPE150                               | 24           |
| 2"              | PPE200                               | 24           |
| 3"              | PPE300                               | 24           |
| 4"              | PPE400                               | 8            |

## Type F Adapters

### Adapter x Male NPT

#### Features

- 1/2" couplers and adapters will interchange with 3/4" couplers and adapters, only the threads and barbs are 1/2"
- 1-1/4" couplers and adapters will interchange with 1-1/2" couplers and adapters, only the threads and barbs are 1-1/4"
- NOT recommended for use with PTFE gaskets, polypropylene cam & groove should not be mixed with metal fittings



#### Specification

- Maximum operating pressure: **125 PSI** (1/2" - 1"), **100 PSI** (1-1/4" - 2"), **60 PSI** (3"), and **50 PSI** (4"); recommendations based on the use of mating Dixon fittings at an ambient temperature of **70°F (21°C)** with standard seal installed



| Size            | Glass-Filled Polypropylene<br>Part # | Optional Qty |
|-----------------|--------------------------------------|--------------|
| 3/4" x 1/2"     | PPF50                                | 24           |
| 3/4"            | PPF75                                | 24           |
| 1"              | PPF100                               | 24           |
| 1-1/2" x 1-1/4" | PPF125                               | 24           |
| 1-1/2"          | PPF150                               | 24           |
| 2"              | PPF200                               | 24           |
| 3"              | PPF300                               | 24           |
| 4"              | PPF400                               | 8            |