

Universal Couplings..... 186-195

Air King®	186-187
Global Air King	188-189
Air King with ferrule	190
Air King with gauge port	190
Air King universal swivels	190
Global Air King ferrules	191
Air King clamps	191
Air King accessories	192
Sand Blast	193
Sure-Lock®	194-195

Quick Disconnects..... 196-231

Dix-Lock® N-Series	196-199
Dual-Lock P-Series	200-202
DF-series	203-207
J-series	208-209
M-series	210-211
CJ-series	212
SHD-series	213-214
L-series	214
U-series	215
NK-series	216
BR-series	217
A-series	218-219
Profile Chart	220
Ball swivel plug	220
Air Chief industrial	221-224
Air Chief plugs	221-222
Air Chief semi-automatic	223
Air Chief automatic	224
Parker E-z-mate	225
Legris automatic safety couplers	226
Air Chief automotive	227-228
Air Chief ARO interchange	229-230
Air Chief Lincoln interchange	231

Steel 3500 nipples..... 232**Bent Stem Swivels..... 233****D.O.T. Air Brake 234-245**

D.O.T. push-in fittings	234-235
Legris D.O.T. push-in fittings	236-239
Air brake	240-245

Push-in..... 246-264

Brass	246-249
Stainless steel Legris	250-251
Nickel-plated brass Legris	252-253
Nylon / Nickel-plated brass Legris	254-256, 258
Nylon Legris	257
Manifold, Legris	258
Fittings kit, Legris	258
Valves	259-261
Ball	259
Quick exhaust	259
Flow control	259-260
Check	261
Metric	262-264

⚠ WARNING

The constant vibration created by air tools, like air drills and pavement breakers, is destructive to air hose couplings, especially the quick-acting type. To provide protection against coupling breakage and related hazards, Dixon® recommends the use of a whip hose. To construct a whip hose, connect one end of a short (3' to 10') air hose to the air tool using a 3500 type steel nipple. Connect the other end of the hose to the air supply using the standard quick-acting coupling. The heat-treated 3500 nipple will withstand vibration far better than the standard coupling and provide a safer connection. The whip hose should remain permanently connected to the tool.