

Safety Cables 267-269

King Cable®	267
Nylon safety restraints	268
King safety whipsnocks	269
King safety shackles	269
ASME air receiver manifold with King safety whipsnocks	269

Air Tanks and Manifolds 270-273

ASME air receiver manifolds	270-271
Whip hose assemblies	271
Manifolds	272-273
Compressor Y	273
Lubricants	273

In-Line Lubricators and Filters 274-275

Lubricators	274
Air filter	274
Nipple filters	275
Lubricator with filter	275
Mini lubricators	275

Valves, Mufflers, and Vents..... 276-292

Safety check valves	276
Conical mufflers	277
Speed control mufflers	277
Breather vents	277
Quiet flow economy pneumatic silencers/mufflers	278
Keychain	278
Mini in-line filter	278
General purpose regulators	278
Needle valves	279
Desiccant dryer	279
Button and tank filler valves	280
Brass lever external drains	280
Brass external drain cocks	280
Safety pop-off valves	281
Flow control valves	282
Series C check valves	282

Blow guns 283-287

Safety	283-284
Pistol Grip	284
Non-Safety	285-286
Heavy duty	286
High volume	286-287

Air Hose..... 288-289

Coil-Chief self-storing	288
Polyurethane	288-289
Industrial coupler blow gun	289

Tire pressure gauges..... 290

LockNLube.....	291
----------------	-----

Swivels 292

Ball	292
In-line	292
Air tool	292

Hose Reels..... 293-297

Low pressure hose reel	293-295
High pressure hose reel	295
Reelcraft®	296-297
5000-Series	296
7000-Series	296
80000 Series	297
30000 manual driven	297

FRLs 298-348

Wilkerson	298-327
Miniatures	298-301
Filters	302-306
Manual in-line desiccant dryer	307
Regulators	308-311
Filter / regulator	312-313
Lubricators	313-316
Combination units	316-320
Exhaust mufflers	320
Automatic drains	321
Lockout valves	321
Accessories and repair kits	322-326
Series 1	327-348
Miniatures	327-329
Filters	329-332
Regulators	333-336
Filter / regulators	336-338
Lubricators	338-341
Combination units	342
Automatic drains	343
Accessories and repair kits	343-348

⚠ WARNING

The constant vibration created by air tools, like air drills and pavement breakers, is destructive to air hose couplings, especially the quick-acting type. To provide protection against coupling breakage and related hazards, Dixon® recommends the use of a whip hose. To construct a whip hose, connect one end of a short (3' to 10') air hose to the air tool using a 3500 type steel nipple. Connect the other end of the hose to the air supply using the standard quick-acting coupling. The heat-treated 3500 nipple will withstand vibration far better than the standard coupling and provide a safer connection. The whip hose should remain permanently connected to the tool.