

VEP-BOP Series Hydraulic Couplings

Female Threaded Couplers

Features

- · Red powder coated components and external O-rings for easy BOP service identification
- Blowout preventer (BOP) coupling contain FKM seals
- Interchangeable with Stucchi VEP/VEP-HD Series, DNP FSI-BOP Series

Material

• Steel components are plated using ROHS compliant zinc nickel

Specification

• Pressure rating 5000 PSI at 70°F (21°C)

Approval

• BOP couplings have been fire tested and Lloyd's certified to **1300°F (700°C)** in accordance with API 16D. Certificate available upon request.

	r chiale micadea ooupiers		
Body Size	Threads	Steel Part #	•
3/8"	3/8" - 18 NPTF	3VEPF3-BOP	
1/2"	1/2" - 14 NPTF	4VEPF4-BOP	-
3/4"	3/4" - 14 NPTF	6VEPF6-BOP	-
1"	1" - 11-1/2 NPTF	8VEPF8-BOP	-
1-1/4"	1-1/4" - 11-1/2 NPTF	10VEPF10-BOP	-
1-1/2"	1-1/2" - 11-1/2 NPTF	12VEPF12-BOP	-



	Female Threaded Plugs		
Body Size	Threads	Steel Part #	
3/8"	3/8" - 18 NPTF	VEP3F3-BOP	
1/2"	1/2" - 14 NPTF	VEP4F4-BOP	
3/4"	3/4" - 14 NPTF	VEP6F6-BOP	
1"	1" - 11-1/2 NPTF	VEP8F8-BOP	
1-1/4"	1-1/4" - 11-1/2 NPTF	VEP10F10-BOP	
1-1/2"	1-1/2" - 11-1/2 NPTF	VEP12F12-BOP	

