# **Block and Bleed Needle Valves**

#### **Features**

- Allows pressure to be bled off without disturbing the permanent piping installation, allowing quick and easy removal or replacement of instruments
- FKM 0-ring seal and PTFE back-up ring below the threads protects from corrosion and galling
- Stem threads are rolled for strength and ease of operation

#### Material

· Stems: 316 stainless steel

## **Specifications**

- Metal-to-metal hard seat design is 100% helium leak tested to 1 x 10-4 ml/s at 200 PSI
- Orifice size is 0.187", flow coefficient: 0.44
- 0.090" bleed hole located on bottom is controlled by a 1/4"-20 UNF-2A bleed screw



## **Hard Seat Male to Female**

NPT Size	Handle Style	PSI @ 200°F	Zinc Nickel Plated Steel Part #	316 Stainless Steel Part #
1/4" - 18	T design	10000	MFC602	MFS602
1/2" - 14	T design	10000	MFC604	MFS604



#### **Soft Seat Male to Female**

NPT Size	Handle Style	PSI @ 200°F	Zinc Nickel Plated Steel Part #	316 Stainless Steel Part #
1/4" - 18	T design	6000	MFC702	MFS702
1/2" - 14	T design	6000	MFC704	MFS704

## **Bleed Needle Valves**

#### **Features**

- Convenient way to relieve process pressures trapped between a shut-off valve and the instrument
- FKM O-ring seal and PTFE back-up ring below the threads protects from corrosion and galling
- Stem threads are rolled for strength and ease of operation

#### Material

· Stems: 316 stainless steel

### **Specifications**

- Metal-to-metal hard seat design is 100% helium leak tested to 1 x 10-4 ml/s at 200 PSI
- Non-rotating soft tip stem and a backup metalto-metal seal
- 0.159" bleed port



316 stainless

## **Hard Seat Male**

NPT Size	Handle Style	PSI @ 200°F	Zinc Nickel Plated Steel Part #	316 Stainless Steel Part #
1/4" - 18	T design	10000	MC802	MS802
1/2" - 14	T design	10000	MC804	MS804



316 stainless

# **Soft Tip Male**

877.963.4966 • dixonvalve.com

NPT Size	Handle Style	PSI @ 200°F	Zinc Nickel Plated Steel Part #	316 Stainless Steel Part #
1/4" - 18	T design	6000	MC852	MS852
1/2" - 14	T design	6000	MC854	MS854