



DX60-Series Hygienic Tanker Valves

Applications

- Used on food-grade stainless steel bulk transport trailers to safely and hygienically load and unload various products including milk, juices, chocolate, glycerin, and many types of food-grade oils

Size

- 3" and 6" x 3"

Features

- Valve housing machined from solid bar
- Hygienic single-acting wiper seal improves cleanability and durability
- Easy-lock plunger for locking valve in open position
- Patented closure system to eliminate the pinch point
- Bonnet design uses standard sanitary clamp for easy removal

Materials

- Product contact material: 304 stainless steel
- Product contact seals: 3A and FDA grade FKM or nitrile rubber
- Cover: aluminum

Specifications

- Holding pressure: 75 PSI
- Surface I.D. finish: <32Ra
- Connections: flange x male threaded bevel and Triclamp x male threaded bevel
- Temperature range: -20°F to 212°F (-28.9°C to 100°C)

Approval

- 3A-Authorization Number 1655, 53-07 (Compression-Type Valves) for CIP and COP



Lanyard style dust cover nut



5/8 UNC threaded post and nut

Size	Connections	Cover Style	Freeze Rod	Material	Part #
3"	150# flange x male threaded bevel seat	With aluminum cover (lanyard style dust cover nut)	with freeze rod	304, nitrile rubber	DX603010A1GB1R
				304, FKM	DX603010A1GV1R
			without freeze rod	304, nitrile rubber	DX603010A1GB1
				304, FKM	DX603010A1GV1
		With aluminum cover (5/8 UNC threaded post and nut)	with freeze rod	304, nitrile rubber	DX603010A1GB3R
				304, FKM	DX603010A1GV3R
			without freeze rod	304, nitrile rubber	DX603010A1GB3
				304, FKM	DX603010A1GV3
		Without aluminum cover	with freeze rod	304, FKM	DX603010A1GV2R
				304, nitrile rubber	DX603010A2GB2R
			without freeze rod	304, nitrile rubber	DX603010A1GB2
				304, FKM	DX603010A1GV2
6" x 3"	threaded bevel seat	Without aluminum cover	without freeze rod	304, FKM	DX6063N10A1GV2



DX603010A1GV1R

For other configurations, contact Dixon Sanitary at 800.789.1718