

# Non-collapsible Hose

# **Chemical Booster Hose - Red**

Working pressure: 800 PSI

#### Size

• 3/4" diameter hose is coupled with 1" threaded couplings

### Approval

Specification

Meets and exceeds NFPA standard 1961



#### Feature

• Reinforced with multiple plies of high tensile Aramid yarn providing flexible strength

#### Materials

- Outer cover material: specially compounded red EPDM tough cover
- · Inner tube material: smooth black synthetic EPDM rubber

### Coupled with female and male NST (NH) thread, chromed brass hole type couplings

Size	Length	Part #
3/4"	50'	80B07-50HCF
	100'	80B07-100HCF
]"	50'	80B10-50HCF
	100'	80B10-100HCF

# Coupled with female and male NST (NH) thread, hole type coupling, aluminum expansion ring couplings

Size	Length	Part #
3/4"	50'	80B07-50HAF
3/4	100'	80B07-100HAF
1"	50'	80B10-50HAF
	100'	80B10-100HAF

#### Features

- Outer construction is designed to withstand abrasion
- Consult Dixon<sup>®</sup> for pricing and availability of other lengths, threads, and configurations
- · Also available with chrome brass fittings

#### Fire and Utility Hose - Red Specifications

- Working pressure: 200 PSI at ambient temperature 70°F (21°C)
- Burst pressure: 600 PSI at ambient temperature 70°F (21°C)

# Coupled with female and male NST (NH) thread, rocker lug, brass expansion ring couplings

Size	Length	Part #
1-1/2"	50'	15B15-50RBF
1-1/2	100'	15B15-100RBF



# Coupled with female and male NST (NH) thread, rocker lug, aluminum expansion ring couplings

Size	Length	Part #
1-1/2"	50'	15B15-50RAF
	100'	15B15-100RAF



# Coupled with female and male NPSH thread, rocker lug, aluminum expansion ring couplings

Size	Length	Part #	
1-1/2"	50'	15B15-50RAS	
	100'	15B15-100RAS	Server and

