

Viper® Select Gallonage Nozzles

Feature

- Four gallonage selection rings **30, 60, 90, and 125 GPM**

Material

- Constructed of E-Lite® aluminum and brass internals

Specification

- Standard operating pressure **300 PSI** maximum



| Size | Thread | GPM @ 100 PSI | Part # |
|--------|--------|---------------|----------|
| 1-1/2" | NST | 30 - 125 | DSG3012F |
| | NPSH | | DSG3012S |

Feature

- Four gallonage selection rings **15, 30, 50, and 60 GPM**

| Size | Thread | GPM @ 100 PSI | Part # |
|--------|--------|---------------|----------|
| 1-1/2" | NST | 15 - 60 | DSG1560F |
| | NPSH | | DSG1560S |

Viper Select Gallonage Low Flow Nozzles

Features

- Four gallonage selection rings **5, 10, 25, and 40 GPM**
- Available without pistol grip

Material

- Constructed of E-Lite aluminum and brass internals

Specification

- Standard operating pressure **300 PSI** maximum



| Size | Thread | GPM @ 100 PSI | Part # |
|------|--------|---------------|---------|
| 1" | NST | 5 - 40 | DSG540F |
| | NPSH | | DSG540S |

Viper Constant Gallonage Nozzles

Features

- Full-time swivels and spinning teeth
- BIMATIC flush system allows flush without shutting down
- Removable pistol grip

Material

- Constructed of E-Lite aluminum and brass internals

Specification

- Standard operating pressure: **100 PSI** (optional pressures of **50** or **75 PSI**)



Approvals

- EN 15182-2 TYPE 3 certified
- NFPA 1964 Compliant

| Size | Thread | GPM @ 100 PSI | Part # |
|--------|--------|---------------|---------|
| 1-1/2" | NST | 60 - 95 | DVS95F |
| | NPSH | | DVS95S |
| 2-1/2" | NST | 150 - 200 | DVS250F |
| | NPSH | | DVS250S |

N