

Factory Set Pressure Reducing Brass Angle Valves

Features

- True combination shut-off and pressure reducing valves
- Female x female valves have an open / closed indicator bonnet for confirmation of status
- Tamper resistant and automatic
- Available with a tamper proof switch
- All debris must be flushed from the system prior to being placed into service 
- Complete switch, bracket, and housing available for field mounting; consult Dixon® for price and availability
- Other configurations are available, contact Dixon for additional information

Specification

- 1-1/2" reduces inlet pressure of **300 PSI (2069 kPa)** or less to working pressures of **10 through 175 PSI (69-1207 kPa)**; 2-1/2" reduces inlet pressures of **400 PSI (2758 kPa)** or less to working pressures of **20 - 175 PSI (138-1207 kPa)** under discharge or static conditions

Approvals

- UL listed for Automatic Sprinkler Systems as floor or zone control valves
- Standpipe Systems, Class I, II and III
- Automatic Check Valve for Dual Riser Systems
- Approved by New York City Board of Standards and Appeals, approval # MEA 54-07-E
- Approved by City of Los Angeles and the City of San Francisco (ULC 2½")

Female x Male

| Inlet Female NPT | Outlet Male NST (NH) | Cast Brass Part # |
|------------------|----------------------|-------------------|
| 1-1/2" | 1-1/2" | NAPRAV150F-15 |
| | | NAPRAV150F-20 |
| | | NAPRAV150F-25 |
| | | NAPRAV150F-30 |
| | | NAPRAV150F-35 |
| | | NAPRAV150F-40 |
| | | NAPRAV150F-45 |
| | | NAPRAV150F-50 |
| 2-1/2" | 2-1/2" | NAPRAV250F-55 |
| | | NAPRAV250F-60 |
| | | NAPRAV250F-65 |
| | | NAPRAV250F-70 |
| | | NAPRAV250F-75 |
| | | NAPRAV250F-80 |
| | | NAPRAV250F-85 |
| | | NAPRAV250F-90 |
| | | NAPRAV250F-95 |



N