

## FloMAX Diesel Fuel Gravity Fill Receivers

### Features

- Used with the FN600 or FN600BL to convert to gravity fueling
- Allows transfer of fluid without using a standard fuel receiver
- Fits standard 1-1/2" fuel receivers

| Size   | Description | Part #  |
|--------|-------------|---------|
| 1-1/2" | straight    | GFR-0   |
|        | 45°         | GFR-45  |
|        | 90°         | GFR-90  |
| 1"     | straight    | GFR1-0  |
|        | 45°         | GFR1-45 |
|        | 90°         | GFR1-90 |




C

## FloMAX Fuel Vents

### Features

- 2" male NPT
- Billet cap provides superior impact resistance
- Easily serviced all metal construction
- Rigid ball cage for positive seal
- Available with: threaded outlet, half coupling, and anti-vandalism mounting

| Description                           | Part # |
|---------------------------------------|--------|
| vent with 5" tube                     | VT     |
| vent with 7" tube                     | VT7    |
| vent with 9" tube                     | VT9    |
| vent with 5" tube and threaded outlet | VTT    |



## FloMAX High-Flow Fuel Vents

### Features

- 7" tubes are available, contact Dixon® for more information
- Rotatable vent top is available
- Capable of handling **400 GPM** fluid flows
- Fits standard 2" NPT openings

| Description                      | Part # |
|----------------------------------|--------|
| high flow fuel vent with 5" tube | VTX    |
| high flow fuel vent with 9" tube | VTX-9  |



## FloMAX Diesel Fuel Swivels

### Features

- Stainless steel male threaded base and ball bearings
- Hard black anodized female threaded nut
- Fluorosilicone sealing O-rings

| Thread Size                           | Description | Part #              |
|---------------------------------------|-------------|---------------------|
| 1-1/2" male NPT x 1-1/2" female NPT   | standard    | FNS                 |
| 2" male NPT x 1-1/2" female NPT       | standard    | FNS2                |
| 1-1/2" female NPT x 1-1/2" female NPT | double      | FNSID               |
| 1-1/2" male NPS x 1-1/2" female NPT   | standard    | FN600S <sup>1</sup> |



<sup>1</sup> Used with FN600 or FN600BL