

Dual-Lock P-Series Pneumatic Couplings


Features

- Interchanges with National A type, Campbell Double-Lock, and Thor PHC series couplings
- Spring-loaded interlocking engagement
- Optional locking key prevents sleeve retraction
- Steel componentry is plated using RoHS-compliant trivalent chrome


Specifications

- Working pressure: **300 PSI** at ambient temperature **70°F (21°C)**
- Nitrile rubber seals are standard temperature range **-40°F to 250°F (-40°C to 121°C)**

E



brass



steel



303 stainless

Female Thread Couplers

Body Size	Threads	Brass Part #	Steel Part #	303 Stainless Steel Part #
1/2"	1/2" – 14 NPTF	---	4PF4	---
	3/4" – 14 NPTF	4PF6-B	4PF6	4PF6-S

Female Thread Plugs



brass



steel



303 stainless

Body Size	Threads	Brass Part #	Steel Part #	303 Stainless Steel Part #
1/2"	3/8" – 18 NPTF	---	P4F3	---
	1/2" – 14 NPTF	P4F4-B	P4F4	---
	3/4" – 14 NPTF	P4F6-B	P4F6	P4F6-S
	3/4" – 14 NPTF	---	P4F6-9 ¹	---
	1" – 11-1/2 NPTF	P4F8-B	P4F8	---

¹ Steel/PTFE coating

Male Thread Couplers



steel



303 stainless

Body Size	Threads	Steel Part #	303 Stainless Steel Part #
1/2"	3/8" – 18 NPTF	4PM3	---
	1/2" – 14 NPTF	4PM4	---
	3/4" – 14 NPTF	4PM6	4PM6-S
	3/4" – 14 NPTF	4PM6-9 ¹	---
	1" – 11-1/2 NPTF	4PM8	---

¹ Steel/PTFE coating