

BR-Series Pneumatic Couplings

Feature


- Interchange data: Rectus 21KA, Tomco Series SC, CEJN Series 223

Specifications

- Nitrile rubber seals are standard temperature range -40°F to 250°F (-40°C to 121°C)
- Pressure rating: **300 PSI**

Female Threaded Plugs

Body Size	Threads	Brass Part #
1/8"	1/8" – 27 NPT	BR1F1-B-E-7
	1/8" – 28 BSPP	BR1BF1-B-E-7
	1/4" – 18 NPT	BR1F2-B-E-7
	1/4" – 19 BSPP	BR1BF2-B-E-7



E

Male Threaded Plugs

Body Size	Threads	Brass Part #
1/8"	1/8" – 27 NPT	BR1M1-B-E-7
	1/8" – 28 BSPP	BR1GM1-B-E-7
	1/4" – 18 NPT	BR1M2-B-E-7
	1/4" – 19 BSPP	BR1GM2-B-E-7



Female Threaded Couplers

Body Size	Threads	Brass Part #
1/8"	1/8" – 27 NPT	1BRF1-B-7
	1/8" – 28 BSPP	1BRBF1-B-7
	1/4" – 18 NPT	1BRF2-B-7
	1/4" – 19 BSPP	1BRBF2-B-7



Male Threaded Couplers

Body Size	Threads	Brass Part #
1/8"	1/8" – 27 NPT	1BRM1-B-7
	1/8" – 28 BSPP	1BRGM1-B-7
	1/4" – 18 NPT	1BRM2-B-7
	1/4" – 19 BSPP	1BRGM2-B-7



Hose Barb Plugs

Body Size	Hose I.D.	Brass Part #
1/8"	4mm	BR1S1.25-B-E-7
	6mm	BR1S1.86-B-E-7
	9mm	BR1S2.83-B-E-7



Hose Barb Couplers

Body Size	Hose I.D.	Brass Part #
1/8"	4mm	1BRS1.25-B-7
	6mm	1BRS1.86-B-7
	9mm	1BRS2.83-B-7

