

## Compound Gauges

### Feature

- ASME B40.1, Grade B accuracy ( $\pm 3-2-3$  % accuracy)

### Materials

- Case: ABS plastic, corrosion resistant
- Bourdon tube: bronze
- Socket: brass
- Window: polycarbonate
- Pointer: black aluminum
- Movement: powerflex with polyester segment, designed for extended wear

### Specification

- Temperature range of  $-40^{\circ}\text{F}$  to  $150^{\circ}\text{F}$  ( $-40^{\circ}\text{C}$  to  $66^{\circ}\text{C}$ )



F

Mercury (Hg)	PSI Range	Figure Interval (Hg/PSI)	Minor Gradient (Hg/PSI)	2-1/2" Face 1/4" Center Back Mount Part #	2-1/2" Face 1/4" Lower Mount Part #
30"	0-100	30/10	5/2	---	GL310
	0-160	30/20	5/5	GC210	---
	0-160	30/20	10/10	---	GL110
	0-200	30/20	10/10	---	GL315

## Vacuum Gauges

### Feature

- ASME B40.1, Grade B accuracy ( $\pm 3-2-3$  % accuracy)

### Materials

- Case: ABS plastic
- Bourdon tube: bronze
- Crystal: polycarbonate
- Pointer: black aluminum
- Movement: powerflex with polyester segment, designed for extended wear

### Specification

- Temperature range:  $-40^{\circ}\text{F}$  to  $150^{\circ}\text{F}$  ( $-40^{\circ}\text{C}$  to  $66^{\circ}\text{C}$ )



Mercury (Hg)	Figure Interval (Hg/PSI)	Minor Gradient (Hg/PSI)	2" Face 1/4" Lower Mount Part #	2" Face 1/4" Center Back Mount Part #	2-1/2" Face 1/4" Lower Mount Part #
30"	5"	.5"	GL105	GC205	GL305