

CVV-Series Hydraulic Couplings

Features

- Contact Dixon® for pressure ratings and other technical information.
- Interchangeable with European Screw-Together, Inteva® STG-Series, Faster® CVV-Series, DNP PVV3, Voswinkel® Type-HS

Specification

- Nitrile rubber seal standard, providing a temperature range of -13°F to 257°F (-25°C to 125°C)

European Female Threaded Couplers



Body Size	Threads	Steel Part #
1/4"	1/4" – 18 NPTF	2CVVF2
	1/4" – 19 BSPP	2CVVBF2
	M14X1.5	2CVVFM1415
3/8"	3/8" – 18 NPTF	3CVVF3
	3/8" – 19 BSPP	3CVVBF3
	M16X1.5	3CVVFM1615
1/2"	1/2" – 14 NPTF	4CVVF4
	3/4" – 16 ORB	4CVVOF4
	1/2" – 14 BSPP	4CVVBF4
	M18X1.5	4CVVFM1815
	7/8" – 14 ORB	4CVVOF5
3/4"	M22X1.5	4CVVFM2215
	3/4" – 14 NPTF	6CVVF6
	3/4" – 14 BSPP	6CVVBF6
1"	M22X1.5	6CVVFM2215
	1" – 11-1/2 NPTF	8CVVF8
	1" – 11 BSPP	8CVVBF8
1-1/4"	1-1/4" – 11-1/2 NPTF	10CVVF10
	1-1/4" – 11 BSPP	10CVVBF10

European Female Threaded Plugs



Body Size	Threads	Steel Part #
1/4"	1/4" – 18 NPTF	CVV2F2
	1/4" – 19 BSPP	CVV2BF2
	M14X1.5	CVV2FM1415
3/8"	3/8" – 18 NPTF	CVV3F3
	3/8" – 19 BSPP	CVV3BF3
	M16X1.5	CVV3FM1615
1/2"	1/2" – 14 NPTF	CVV4F4
	3/4" – 16 ORB	CVV4OF4
	1/2" – 14 BSPP	CVV4BF4
	M18X1.5	CVV4FM1815
	7/8" – 14 ORB	CVV4OF5
3/4"	M22X1.5	CVV4FM2215
	3/4" – 14 NPTF	CVV6F6
	3/4" – 14 BSPP	CVV6BF6
1"	M22X1.5	CVV6FM2215
	1" – 11-1/2 NPTF	CVV8F8
	1" – 11 BSPP	CVV8BF8
1-1/4"	1-1/4" – 11-1/2 NPTF	CVV10F10
	1-1/4" – 11 BSPP	CVV10BF10

K